



**LXIX
OTWARTE
SEMINARIUM
Z AKUSTYKI**

69th Open Seminar of Acoustics OSA2023

**5th Polish-German Structured Conference
on Acoustics PGSCA 2023**

Karpacz, 25-29 September 2023

KSIAŻKA ABSTRAKTÓW • BOOK OF ABSTRACTS

WSPÓŁORGANIZATORZY ▪ CO-ORGANIZERS



Politechnika
Wrocławska



WSPIERAJĄ NAS ▪ SUPPORT US



ORGANIZATORZY ▪ ORGANIZERS

- Wrocław Branch Polish Acoustical Society
- Department of Acoustics, Multimedia and Signal Processing,
Wrocław University of Science and Technology
- Committee on Acoustics, Polish Academy of Sciences
- Svantek
- KFB Acoustics
- Instytut Techniki Budowlanej
- Acoustics Research Laboratory

KOMITET NAUKOWY ▪ SCIENTIFIC COMMITTEE **69TH OPEN SEMINAR OF ACOUSTICS OSA2023**

Chairman: prof. dr hab. inż. Krzysztof J. Opieliński
dr inż. Filip Barański, Prezes KFB Acoustics
prof. dr hab. inż. Wojciech Batko
dr hab. inż. Dariusz Bismor, prof. PŚ
prof. dr hab. inż. Adam Brański
prof. dr hab. inż. Andrzej Dobrucki
prof. dr hab. Marzena Dzida
dr hab. Barbara Gambin, prof. IPPT
prof. dr hab. inż. Tadeusz Gudra
dr hab. inż. Marek Iwaniec, prof. AGH
dr hab. Arkadiusz Józefczak, prof. UAM
dr hab. inż. Tadeusz Kamisiński, prof. AGH
prof. dr hab. inż. Piotr Kleczkowski
prof. dr hab. inż. czł. koresp. PAN Bożena Kostek
prof. dr hab. inż. czł. koresp. PAN Eugeniusz Kozaczka
prof. dr hab. inż. Lucyna Leniowska
prof. dr hab. Bogumił Linde
prof. dr hab. Jerzy Litniewski
dr hab. inż. Jacek Marszał, prof. PG
prof. dr hab. inż. Mirosław Meissner
prof. dr hab. Andrzej Miśkiewicz
prof. dr hab. inż. czł. rzecz. PAN Andrzej Nowicki
prof. dr hab. inż. czł. koresp. PAN Marek Pawełczyk
dr hab. inż. Janusz Piechowicz, prof. AGH
dr inż. Przemysław Plaskota
dr hab. inż. Dariusz Pleban, prof. CIOP-PIB
prof. dr hab. Anna Preis
prof. dr hab. inż. Tadeusz Pustelny
prof. dr hab. inż. Zbigniew Ranachowski
prof. dr hab. inż. Wojciech Rdzanek
prof. dr hab. inż. Andrzej Stepnowski

dr hab. Ewa Skrodzka, prof. UAM
prof. dr hab. Anna Snakowska
prof. dr hab. inż. Stefan Weyna
prof. dr hab. inż. Jerzy Walerian Wiciak
dr hab. Andrzej Wicher, prof. UAM
dr hab. inż. Franciszek Witos, prof. PŚ
dr hab. inż. Tadeusz Wszolek, prof. AGH
dr hab. inż. Wiesław Wszolek, prof. AGH
dr hab. inż. Janusz Wójcik, prof. IPPT PAN
prof. dr hab. inż. Jan Żera

KOMITET NAUKOWY ▪ SCIENTIFIC COMMITTEE
5TH POLISH-GERMAN STRUCTURED CONFERENCE ON ACOUSTICS 2023

Chairmen:

Andrzej Dobrucki, Wrocław University of Science and Technology, Poland
Michael Vorländer, RWTH Aachen, Germany

Members:

Jan Abshagen, Marine Centre Kiel, Germany
Daniel Beer, Fraunhofer Idmt Ilmenau, Germany
André Fiebig, Tu Berlin, Germany
Arkadiusz Józefczak, Adam Mickiewicz University In Poznań, Poland
Iwona Kochańska, Gdańsk University Of Technology, Poland
Jędrzej Kociński. Adam Mickiewicz University In Poznań, Poland
Piotr Majdak, Academy Of Science, Vienna, Austria
Jacek Marszał, Gdańsk University of Technology, Poland
Reinhard Neubauer, IBN Ingolstadt, Germany
Elżbieta Nowicka, ITB Warsaw, Poland
Anna Preis, Adam Mickiewicz University in Poznań, Poland
Heinrich Ruser, Universität Der Bundeswehr, München, Germany
Piotr Staroniewicz, Wrocław University of Science and Technology, Poland
Anna Warzybok, Oldenburg University, Germany
Andrzej Wicher, Adam Mickiewicz University in Poznań, Poland
Tadeusz Wszolek, AGH University of Science and Technology In Cracow, Poland

KOMITET ORGANIZACYJNY ▪ ORGANIZING COMMITTEE

Chairman: Przemysław Plaskota, Ph.D., Wrocław University of Science Technology

Vice-President: Romuald Bolejko, Ph.D., Wrocław University of Science Technology

Secretary: Piotr Staroniewicz, Ph.D., Wrocław University of Science Technology

Treasurer: Paweł Dziechciński, Ph.D., Wrocław University of Science Technology;

Members of the organizing committee:

prof. Andrzej Dobrucki, Wrocław University of Science Technology;

prof. Jerzy Wiciak, AGH Kraków, Poland

prof. Michael Vorländer, RWTH Aachen, Germany;

Stefan Brachmanski, Ph.D., Wrocław University of Science and Technology

Maurycy Kin, Ph.D., Wrocław University of Science and Technology

Piotr Kozłowski, Ph.D., Wrocław University of Science and Technology

Bartłomiej Kruk, Ph.D., Wrocław University of Science and Technology

Michał Łuczyński, Ph.D., Wrocław University of Science and Technology

Tomasz Świetlik, Ph.D., Wrocław University of Science and Technology

Elżbieta Nowicka Ph.D., Instytut Techniki Budowlanej

Agnieszka Wielgus Ph.D., Wrocław University of Science and Technology

Tomasz Malec Ph.D., KFB Acoustics

Aleksandra Klimek., Wrocław University of Science and Technology

Tomasz Nowak., Wrocław University of Science and Technology

Agata Zatorska., Wrocław University of Science and Technology

Dominika Kuczak., Wrocław University of Science and Technology

Tomasz Kopciński., Wrocław University of Science and Technology

Jan Kucharczyk., Wrocław University of Science and Technology

Mirosław Miazga., Wrocław University of Science and Technology

Karol Sałagan, Svantek

Monday, 25.09.2023					
		Room 100	Plenary Room	Room 70	Room 50
08:00	Reception desk	PTA Delegates assembly			
08:20					
08:40					
09:00					
09:20					
09:40					
10:00					
10:20					
10:40					
11:00					
11:20					
11:40					
12:00		Tutorial SPS dr Mark E. Davis	Tutorial SPS dr. Ivan Seleznov		
12:20					
12:40					
13:00					
13:20	Welcome reception	PTA Delegates assembly	IEEE Ceremonial lunch	Lunch SPS	
13:40					
14:00					
14:20					
14:40					
15:00			Tutorial SPS prof. Gaspare Galati (online)		
15:20					
15:40			coffee break		
16:00					
16:20			Tutorial SPS dr. Diego Cristallini		
16:40					
17:00					
17:20					
17:40					
18:00					
18:20					
18:40					
19:00					
20:00					
21:00					

Tuesday, 26.09.2023							
		Room 100	Plenary Room		Room 70	Room 50	
08:00	Registration desk	Breakfast (only for Sandra SPA guests)					
08:20							
08:40							
09:00		OSA + POLGER+SPS Opening IEEE SPS and AESS Presidents					
09:20		OSA+SPS Plenary 1 prof. Olivier Adam					
09:40							
10:00		OSA opening prof. W. Batko (in Polish)			Group photo coffee break		
10:20							
10:40		OSA Environmen tal acoustics 10 28 36	POLGER Building acoustics 13 17 94		SPS RADAR 1 Keynote F. Yanovsky	SPS Medical	
11:00							
11:20		coffee break					
11:40							
12:00		OSA Environmen tal acoustics 50 64 116	POLGER Building acoustics 35 106 107	Lunch SPS			
12:20							
12:40		Poster session 45 126 2 26 87 14 59 31 115 132 41					
13:00							
13:20		Lunch OSA		SPS Plenary 1 prof. Athena Petropulu			
13:40							
14:00		Industrial session					
14:20							
14:40		OSA Plenary prof. Marzena Dzida				coffee break	
15:00							
15:20		Industrial session Barrisol Commercial Audio				SPS PASSIVE RADAR	SPS AI
15:40							
16:00		coffee break					
16:20							
16:40	OSA Bio & Speech acoustics 30 88 7	POLGER Electro acoustics 22 38 39	OSA+SPS Plenary 2 prof. Artur Lorens				
17:00							
17:20	Gala dinner (up to 24.00)						
17:40							
18:00							
18:20							
18:40							
19:00	Gala dinner (up to 24.00)						
20:00							
21:00							

Wednesday, 27.09.2023						
		Room 100	Plenary Room	Room 70	Room 50	Room 30
08:00	Reception desk	Breakfast (only for Sandra SPA guests)				
08:20						
08:40						
09:00		OSA Plenary prof. André Fiebig		SPS Signal Processing 1 Keynote S. Basu	SPS Comm&Loc	
09:20						
09:40		OSA Commemorative session prof. Grażyna Grelowska				
10:00		coffee break			coffee break	OSA Marek Kwiek Competition 33 25 47 78
10:20						
10:40		OSA Physical acoustics 79 71 114	POLGER Hydro acoustics 58 73 63			
11:00		coffee break		SPS Signal Processing 2 Keynote P. Dewilde	SPS SAR/ISAR	coffee break
11:20						
11:40						
12:00		OSA Speech & Building acoustics 86 117 65 15	POLGER Hydro acoustics 54 51 27 67	Lunch SPS		OSA Marek Kwiek Competition 6 113 3 72
12:20						
12:40						
13:00		Poster session PTA 60th Anniversary		SPS Plenary 2 dr. Maciej Łopatka		
13:20		Lunch OSA				
14:00						
14:20		OSA Plenary prof. Iwona Kochańska		coffee break		
14:40						
15:00		Industrial session Yamaha Acoustic Enhancement		SPS RADAR 2	SPS Communi cations	
15:20						
15:40						
16:00	OSA Hydro acoustics 52 103 74	POLGER Electro acoustics 24 32 99	OSA+SPS Plenary 3 R2Commemorative session prof. Wiesław Barwicz (in Polish)			
16:20						
16:40						
17:00						
17:20						
17:40						
18:00						
18:20						
18:40						
19:00						
20:00	Bonfire (up to 24.00)					
21:00						

Thursday, 28.09.2023					
		Room 100	Room 70	Plenary Room	Room 50
08:00	Reception desk	Breakfast (from 7.15) (only for Sandra SPA guests)			
08:20					
08:40					
09:00		Trips		SPS Implementations and HW	
09:20					
09:40					
10:00					
10:20					
10:40					
11:00			coffee break		
11:20			SPS Plenary 4 dr. Mark E. Davis		
11:40					
12:00			Conference closing SPSympo		
12:20					
12:40			Lunch SPS		
13:00					
13:20		Lunch OSA			
13:40					
14:00			Measurements of the sound level in rooms		
14:20			Warsztaty Pomiary akustyczne w pomieszczeniach		
14:40					
15:00					
15:20			coffee break		
15:40					
16:00	OSA Building acoustics 18 19 20 23	POLGER Ultrasound 46 40 60 61	Workshop Strategic noise maps	OSA Speech & Signal acoust. 48 4 16	
16:20					
16:40					
17:00					
17:20	coffee break				
17:40	OSA Building acoustics 80 109 62	POLGER Env. acoustics 66 77			
18:00	Warsztaty Strategiczne mapy hałasu				
18:20					
18:40					
19:00	Dinner				
20:00					
21:00					

Friday, 29.09.2023					
		Room 100	Room 70	Plenary Room	Room 50
08:00	R e c e p t i o n d e s k	Breakfast (only for Sandra SPA guests)			
08:20					
08:40					
09:00		OSA Noise & Vibro acoustics 68 43 111	POLGER Psycho acoustics 83 92 95	Acoustic approvals of residential buildings in Poland Warsztaty Odbiory akustyczne budynków mieszkalnych w Polsce	
09:20					
09:40					
10:00		coffee break			
10:20		OSA Noise & Vibro acoustics 37 49	POLGER Psycho acoustics 8 81 55		
10:40					
11:00					
11:20		coffee break			
11:40		OSA Noise & Vibro acoustics 34 53 90	POLGER Speech acoustics 1 5 75		
12:00					
12:20					
12:40					
13:00	Closing ceremony OSA2023				
13:20					
13:40					
14:00	Lunch OSA				
14:20					
14:40					

PONIEDZIAŁEK

25.09.2023

MONDAY

10:00–12:40 PTA Delegates assembly *Room 100*

14:00–15:00 Lunch PTA DA

13:40–18:40 PTA Delegates assembly *Room 100*

19:00–22:00 Welcome reception(starters + glass of wine/beer)

WTOREK

26.09.2023

TUESDAY

09:00–09:40 OSA+SPS Opening IEEE SPS and AES Presidents, Plenary Room

09:40–10:20 OSA+SPS Plenary 1 prof. Olivier Adam, Plenary Room, Chairman: Piotr Samczyński

10:20–11:00 OSA opening prof. W. Batko 89, Plenary Room, Chairman: Jerzy Wiciak

- BATKO, Wojciech Michał

Diagnosis of acoustic hazards of the environment and its identification problems (ID: 89)

11:00–12:00 OSA Environmental acoustics 10 28 36, Room 100, Chairman: Cezary Kasprzak

- Bukala, Michał J; Nowoświat, Artur; Chyla, Andrzej

Residual convolutional neural network for continuous identification of aircraft noise (ID: 10)

- Wiciak, Jerzy; Młynarczyk, Dorota ; Małecki, Paweł; Piechowicz, Janusz

Questionnaires and Acoustic Measurements in Longyearbyen Area, Svalbard (ID: 28)

- Żuchowski, Rafał; Nowoświat, Artur

Assessment of the impact of road traffic noise based on post-realization analysis of a project (ID: 36)

11:00–12:00 POLGER Building acoustics 13 17 94, Plenary Room, Chairman: Elżbieta Nowicka

- Neubauer, Reinhard O.

Acoustic classification with the descriptor of the weighted standardized level difference $D_{nT,w}$ and of the weighted apparent sound reduction index R'_{w} . Are the classes the same? (ID: 13)

- Vorlaender, Michael

Sound insulation – comparison of standard vs. real world situations (ID: 17)

- Nowotny, Łukasz; Nurzyński, Jacek

Estimation of the improvement of the impact sound insulation of a carpet floor covering on a wooden floor based on the results of tests carried out on a massive floor (ID: 94)

12:20–13:20 OSA Environmental acoustics 50 64 116, Room 100, Chairman: Maciej Kłaczyński

- Kasprzak, Cezary

The impact of infrasound on the level of activation (ID: 50)

- Wszolek, Tadeusz; Kłaczyński, Maciej; Pawlik, Paweł; Stępień, Bartłomiej; Małecki, Paweł; Mleczo, Dominik

Tests of windshields for wind turbines noise measurements (ID: 64)

- Staniek, Andrzej C.

Validation of the measurement data for different heights of a microphone position in outdoor environment (ID: 116)

12:20–13:20 POLGER Building acoustics 35 106 107, Plenary Room, Chairman: Reinhard Neubauer

- Nowicka, Elżbieta

Assessment of acoustic quality of residential buildings in Poland - case study (ID: 35)

- Nocke, Christian

Micro-perforated stretched ceilings for acoustic, lighting and climate design (ID: 106)

- Nocke, Christian

New draft DEGA guideline 103-1 in sound protection classes (ID: 107)

13:20–14:00 Poster session 45 126 2 26 87 14 59 31 115 132 41, Chairman: Piotr Kozłowski

- Mleczko, Dominik

The influence of diffusing elements arrangement in a reverberation room on the results of airborne sound insulation measurements (ID: 45)

- Kopciński, Tomasz; Kin, Maurycy J.

Design and practical realization of an amplifier constructed on the basis of NuVistors used in the preamplifier circuit (ID: 126)

- Plaskota, Przemysław

Optimisation of the model for the numerical determination of the HRTF (ID: 2)

- Małecki, Paweł; Pawlaczyk-Łuszczynska, Małgorzata; Wszolek, Tadeusz; Drzymala, Bohdan

Infrasound and Well-being: A Study of Wind Turbine Impact (ID: 26)

- Młynarczyk, Dorota

Investigating the Restorative Properties of Natural Soundscapes (ID: 87)

- Łapka, Wojciech; Jakubowski, Piotr P.

Experimental aeroacoustic studies of selected three types of helicoidal resonators (ID: 14)

- Kosała, Krzysztof

Sound insulation performance of cube-shaped enclosures (ID: 59)

- Wójciak, Kamil; Gaj, Patryk; Kopania, Joanna

Noise Testing of Multi-disc Fan (ID: 31)

- Świrk, Patrycja; Leniowska, Lucyna

Selected acoustic structures for effective sound absorption at low frequencies (ID: 115)

- Radosz, Jan

The effect of ultrasonic noise on a worker's ability to perform their basic tasks (ID: 132)

- Bogusławski, Grzegorz; Kopania, Joanna Maria; Gaj, Patryk; Wójciak, Kamil

Comparison of the acoustic parameters of the commercial ceiling swirl diffusers with the prototype model (ID: 41)

15:00–15:40 OSA Plenary prof. Marzena Dzida 42, Plenary Room, Chairman: Arkadiusz Józefczak

- Dzida, Marzena H.

Molecular structure and thermophysical properties of ionanofluids (ID: 42)

15:40–16:00 Industrial session Barrisol Plenary Room, Chairman: Romuald Bolejko

16:00–16:20 Industrial session Commercial Audio Plenary Room, Chairman: Romuald Bolejko

16:40–17:40 OSA Bio & Speech acoustics 30 88 7, Room 100, Chairman: Krzysztof Opieliński

- Kaczmarek, Katarzyna

Contrast-enhanced magneto-motive ultrasound imaging of sentinel lymph nodes (ID: 30)

- Węglarz, Karolina; WIESŁAW, WSZOŁEK; Szczygiet, Elżbieta; Hemmerling, Daria

Comparative analysis of selected voice parameters of patients with obstructive pulmonary disease and dysphonia. (ID: 88)

- Brachmański, Stefan; Kin, Maurycy J.; Rurzyńska, Natalia

Objective Assessment of the Speech Signal Quality Broadcasted by Local Digital Radio in Selected Locations in Wrocław (ID: 7)

16:40–17:40 POLGER Electroacoustics 22 38 39, Plenary Room, Chairman: Andrzej Dobrucki

- Reszke, Edward R; Dobrucki, Andrzej B.

Electrodynamic pick-up for electric string instruments (ID: 22)

- Lewandowski, Marcin; Augustyniak, Aleksander

First-order ambisonics microphone with MEMS and condenser capsules (ID: 38)

- Pietrzak, Agnieszka

Azimuth and elevation errors in binaural reproduction of ambisonic sound (ID: 39)

17:40–18:20 OSA+SPS Plenary 2 prof. Artur Lorens, Plenary Room, Chairman: Andrzej Dobrucki

- Cochlear Implant – an electronic prosthesis of a sensory organ

09:00–09:40 OSA Plenary prof. André Fiebig, Plenary Room, Chairman: Michael Vorländer

- Environmental noise assessment – do we need different indicators to assess noisy and quiet environments?

09:40–10:20 OSA Commemorative session prof. Grażyna Grelowska, Plenary Room, Chairman: Iwona Kocharńska

10:20–11:40 OSA Marek Kwiek Competition 33 25 47 78, Room 30, Chairman: Stefan Brachmański

- Chojnacki, Bartłomiej; Chojak, Aleksandra; Pawlik, Jan; Binek, Wojciech; Idczak, Julia
Research in the use of metamaterial sound-absorbing structures in electroacoustics (ID: 33)
- Nowak, Tomasz; Dobrucki, Andrzej B.
Simulation of acoustic lens influence on wavefront shaping (ID: 25)
- Kuras, Romuald; Hajder, Sebastian
Experimental validation of the asymmetric PZT optimal shape in the active vibration reduction of triangular plates (ID: 47)
- Pater, Marcin; Grochowina, Marcin A
Identification of errors in the digital transmission paths of radio stations (ID: 78)

10:40–11:40 OSA Physical acoustics 79 71 114, Room 100, Chairman: Andrzej Dobrucki

- Wesołowska, Julia
Wpływ wykorzystania układu rezonatorów w strukturze kryształu sonicznego na jego skuteczność (ID: 79)
- Lasota, Henryk
Infinitesimal volume area of physical space-time in acoustics and electromagnetics (ID: 71)
- Wrzeciono, Piotr; Szymański, Michał; Bayat, Hydayatullah
Algorithm for detection of wave packets in a circular waveguide (ID: 114)

10:40–11:40 POLGER Hydroacoustics 58 73 63, Plenary Room, Chairman: Iwona Kocharńska

- Żak, Andrzej; Studański, Ryszard; Czapiewska, Agnieszka; Wojewódka, Łukasz; Łuksza, Andrzej
Evaluation of hydroacoustic channel stationarity for reciprocal movement of transmitter and receiver (ID: 58)
- Schmidt, Jan H.; Kochanska, Iwona; Schmidt, Aleksander M.
Low-Power Underwater Modem for Shallow Water Communications (ID: 73)
- Klusek, Zygmunt; Lisimenka, Aliaksandr
The nature of the variability of the underwater noise field on the Słupsk Bank. (ID: 63)

12:00–13:20 OSA Marek Kwiek Competition 6 113 3 72, Room 30, Chairman: Stefan Brachmański

- Pondel-Sycz, Karolina Maria

Acoustic model for the classification of Polish vowels (ID: 6)

- Gmyrek, Stanisław; Hossa, Robert; Makowski, Ryszard

Reducing the impact of fundamental frequency on the HFCC parameters of the speech signal (ID: 113)

- Łuczyński, Michał

Preliminary Study: Mobile Phone as a Phonocardiographic Signal Recorder (ID: 3)

- Gawlik, Mateusz

Comparison of the transitional states of singing voice registers depending on the presence of the singer's formant. (ID: 72)

12:00–13:20 OSA Speech & Building acoustics 86 117 65 15, Room 100, Chairman: Paweł Dziechciński

- Wielgus, Agnieszka; Szlachetko, Bogusław; Łuczyński, Michał

Beamforming in nearfield - metaheuristic approach and speech intelligibility tests (ID: 86)

- Szklanny, Krzysztof

Cloning the voice and speech of Piotr Fronczewski for Polish speech synthesis. (ID: 117)

- Dulak, Leszek; Żuchowski, Rafał

Influence of the laboratory measurement method of the reduction of transmitted impact noise by covering floors on a heavyweight standard floor on the result (ID: 65)

- Bolejko, Romuald

Evaluation of the impact of a leak on the sound transmission loss of a building partition using sound intensity measurements (ID: 15)

12:00–13:20 POLGER Hydroacoustics 54 51 27 67, Plenary Room, Chairman: Jan Abshagen

- Abshagen, Jan; Haak, Christian

Sound Propagation Experiments in the Western Baltic Sea (ID: 54)

- Galka, Andreas

Reconstruction of source components from hydroacoustic time series (ID: 51)

- Schmidt, Aleksander M.; Kilian, Lech; Marszał, Jacek

Experimental tests of selected sound-absorbing materials dedicated for a hydroacoustic measuring basin (ID: 27)

- Cymerman, Zuzanna; Kochańska, Iwona

The Simulation of the Influence of the Doppler Effect on Wideband Hydroacoustic Signals (ID: 67)

13:20–14:00 Poster session PTA 60th Anniversary, Chairman: Jerzy Wiciak

15:00–15:40 OSA Plenary prof. Iwona Kochańska 69, *Plenary Room*, Chairman: Jacek Marszal

▪ Kochanska, Iwona

Digital data transmission techniques in shallow-water acoustic communications (ID: 69)

15:40–16:20 Industrial session YAMAHA Acoustic Enhancement, *Plenary Room*, Chairman: Piotr Kozłowski

16:40–17:40 OSA Hydroacoustics 52 103 74, *Room 100*, Chairman: Jacek Marszal

▪ Salamon, Roman; Marszal, Jacek; Kochańska, Iwona

A Tool for Designing Water Tanks for Measuring Hydroacoustic Transducers (ID: 52)

▪ Klusek, Zygmunt; Lisimenka, Aliaksandr

Prediction of effects of impact pile driving noise on marine fauna in the PEEZ: A comparison of different scenarios (ID: 103)

▪ Listewnik, Karol Jakub

A Design of an Acoustic Coupler for Calibration of Pressure Sensors at Ultra Low Frequencies (ID: 74)

16:40–17:40 POLGER Electroacoustics 24 32 99, *Plenary Room*, Chairman: Daniel Beer

▪ Melnikov, Anton; Schenk, Hermann A.G.; Wall, Franziska

Analytical modeling of the harmonic distortion caused by squeeze film damping in MEMS-based acoustic transducers (ID: 24)

▪ Czesak, Karol; Kleczkowski, Piotr

Sound power level as a means of effectiveness of Distributed Mode Loudspeakers (ID: 32)

▪ Beer, Daniel; Männchen, Andreas; Lenk, Claudia; Ziegler, Martin; Ivanov, Tzvetan

A new, bio-inspired microphone design (ID: 99)

17:40–18:40 OSA+SPS Plenary 3 Commemorative session prof. Wiesław Barwicz, *Plenary Room*, Chairman: Wiesław Barwicz

CZWARTEK

28.09.2023

THURSDAY

08:00–18:00 Trip Wroclaw Old Town

08:00–15:00 Trip KFB Acoustics

08:00–15:00 Trip Śnieżka by foot

09:00–13:00 Trip Karpacz by foot or Śnieżka by lift

14:00–15:40 Workshop: Measurements of the sound level in rooms, *Plenary Room*, Chairman: Robert Sokołowski

16:00–19:00 Workshop: Strategic noise maps, *Plenary Room*, Chairman: Tomasz Malec

16:00–17:20 POLGER Ultrasound 46 40 60 61, *Room 70*, Chairman: Arkadiusz Józefczak

▪ Bielas, Rafał; Kubiak, Tomasz; Józefczak, Arkadiusz

The potential of liquid marbles and Pickering droplets as templates for colloidal capsules (ID: 46)

▪ Scheller, Lukasz; Cwynar, Krzysztof; Dzida, Marzena H.

Thermodynamic properties of 1-allyl-3-methylimidazolium dicyanamide and 1-vinyl-3-methylimidazolium bis(trifluoromethylsulfonyl)imide (ID: 40)

▪ Jameel, Bassam M; Bielas, Rafał; Józefczak, Arkadiusz

Magnetic Pickering emulsions characterization by ultrasound attenuation spectroscopy (ID: 60)

▪ Świetlik, Tomasz

Effect on imaging quality of ultrasound probe parameters in Doppler tomography method. (ID: 61)

16:00–17:20 OSA Building acoustics 18 19 20 23, *Room 100*, Chairman: Romuald Bolejko

▪ Nowoświat, Artur; Żuchowski, Rafał; Marchacz, Michał; Olechowska, Marcelina

Acoustic adaptation of ventilation system prototypes dedicated to individual classrooms (ID: 18)

▪ Żuk, Daria; Abramczyk, Norbert ; Jakubowski, Piotr PJ

The influence of composite material manufacturing technology on the change of insulation from impact sounds (ID: 19)

▪ Abramczyk, Norbert ; Żuk, Daria; Jakubowski, Piotr PJ

Acoustic insulation tests of a multi-layer composite modified with rubber recyclete (ID: 20)

▪ Kamisiński, Tadeusz

Acoustic aspects of the modernization project of the Pomeranian Philharmonic in Bydgoszcz (ID: 23)

16:00–17:00 OSA Speech & Signal acoustics 48 4 16, Room 50, Chairman: Piotr Staroniewicz

- Zimny, Kamil

Effect of phase modification of sound components on spatial impression in 2 and 3-component signals
(ID: 48)

- Dziechciński, Paweł

Crowd noise spectra for the calculation of the speech transmission index for public address systems
(ID: 4)

- Pluta, Marek Janusz

Control of spectral components in additive resynthesis as a means to alter sensation of consonance in chords (ID: 16)

17:40–18:40 OSA Building acoustics 80 109 62, Room 100, Chairman: Tadeusz Kamisiński

- Pękala, Piotr

Practical aspects of diffuse reflection and sound diffraction modeling in room acoustics simulations
(ID: 80)

- Turkowska, Hanna

Annoyance of noise penetrating partitions in multi-family and multi-function buildings. (ID: 109)

- Suder-Dębska, Katarzyna

Acoustic aspects of the Goseck Circle area (ID: 62)

17:40–18:20 POLGER Environmental acoustics 66 77, Room 70, Chairman: Tadeusz Wszótek

- Stępień, Bartłomiej; Wszótek, Tadeusz; Mleczek, Dominik; Małecki, Paweł; Pawlik, Paweł;
Kłaczyński, Maciej; Czapla, Marcjanna

Wind turbine noise annoyance prediction in the low-frequency range (ID: 66)

- Wszótek, Tadeusz

Measurement verification of model calculations results of noise distribution around large industrial plants (ID: 77)

PIĄTEK

29.09.2023

FRIDAY

09:00–13:00 Workshop: Acoustic approvals of residential buildings in Poland, *Plenary Room*,
Chairman: Elżbieta Nowicka

09:00–10:00 OSA Noise & Vibroacoustics 68 43 111, *Room 100*, Chairman: Janusz Piechowicz

- Łojek, Paweł; Suder-Dębska, Katarzyna

Investigation of flow features and acoustic radiation of a set of rectangular cavities in a channel
(ID: 68)

- Klimek, Aleksandra; Dobrucki, Andrzej B.

Acoustic metamaterial design for levelling the impact of double-wall resonance on sound insulation
(ID: 43)

- Piechowicz, Janusz

Acoustic screen as a practical anti-noise protection (ID: 111)

09:00–10:00 POLGER Psychoacoustics 83 92 95, *Room 70*, Chairman: Jan Žera

- Majdak, Piotr

Modeling Human Sound-Source Localization: Current State and Future Directions (ID: 83)

- Laback, Bernhard

Contextual Localization Bias For A Wide Range Of Azimuth And Frequency Conditions (ID: 92)

- Sontacchi, Alois; Blöcher, Christian; Hatheier, Thomas

Experimental setup design to evaluate acoustical privacy protection in small enclosed compartments.
(ID: 95)

10:20–11:20 OSA Noise & Vibroacoustics 37 49, *Room 100*, Chairman: Janusz Piechowicz

- Kopania, Joanna Maria; Bogusławski, Grzegorz; Gaj, Patryk; Wójciak, Kamil

Aeroacoustic parameters of the ceiling swirl diffuser with prototype adjustable-blades (ID: 37)

- Korytowski, Adam; Wronka, Wojciech

Test stand for study of reverberating plates with adjustable features (ID: 49)

10:20–11:20 POLGER Psychoacoustics 8 81 55, *Room 70*, Chairman: Piotr Majdak

- Kociński, Jędrzej; Hafke-Dys, Honorata; Grzywalski, Tomasz; Pastusiak, Anna; Biniakowski, Adam; Szarzyński, Krzysztof

Analysis of asthma patients' auscultatory sounds. (ID: 8)

- Kociński, Jędrzej; Wiecher, Andrzej; Pastusiak, Anna; Puchalska, Magdalena; Sudaj, Natalia; Górniak, Marcin

The use of psychoacoustic tests and objective methods of hearing examination in the study of Alzheimer's disease patients (ID: 81)

- Žera, Jan

Profile Analysis: A framework for the study of auditory sound spectrum analysis (ID: 55)

11:40–12:40 OSA Noise & Vibroacoustics 34 53 90, Room 100, Chairman: Piotr Jakubowski

▪ Ilewicz, Grzegorz

Investigation of tribological interactions influence on dynamics of optimal surgical robot with DC motor and PID controller taking into account inputs from in vitro experiments on cardiovascular tissue (ID: 34)

▪ Trojanowski, Roman; Wiciak, Jerzy

Impact of changes in the shape of sensor part of sensor-actuator hybrid on its effectiveness in plates' vibroacoustic reduction (ID: 53)

▪ Małecki, Paweł; Pietrzak, Paula; Perz, Rafał; Zakrzewski, Filip; Matyjewski, Marek

Analysis of Dynamic Mechanical Properties of Composite Materials for Electric Guitar Construction (ID: 90)

11:40–12:40 POLGER Speech acoustics 1 5 75, Room 70, Chairman: Jędrzej Kociński

▪ Staroniewicz, Piotr

Subjective tests of speaker recognition for selected voice disguise techniques (ID: 1)

▪ Kucharski, Mateusz A

Lossy coding and bitrate effects on changes in formant frequencies in Japanese and English speech signals (ID: 5)

▪ Pastusiak, Anna; Kociński, Jędrzej; Warzybok-Oetjen, Anna

Validation of Adaptive Categorical Listening Effort Scaling (ACALES) for Polish language. (ID: 75)

13:00–14:00 Closing ceremony OSA2023, Plenary Room, Chairman: Jerzy Wiciak

Paper ID: 1

Subjective tests of speaker recognition for selected voice disguise techniques

Piotr Staroniewicz (Wroclaw University of Science and Technology)*

Corresponding author: **Piotr Staroniewicz**, piotr.staroniewicz@pwr.edu.pl

Research work on the effectiveness of voice disguise techniques is important for the development of biometric systems (surveillance) as well as phonoscopic research (forensics). A speaker recognition system or a listener can be deliberately or non-deliberately misled by technical or natural methods. It is important to determine the impact of these techniques on both automatic systems and live listeners. This paper presents the results of listening tests conducted on a group of 40 people. The effectiveness of speaker recognition was investigated using selected natural (chosen from four groups of deliberate natural techniques: phonation, phonemic, prosodic and deformation) and technical (pitch shifting, GSM coding) voice disguise techniques. The results were related to the previously obtained outcomes for the automatic method of verification carried out using a classical speaker recognition system based on MFCC (Mel Frequency Cepstral Coefficients) parameterisation and GMM (Gaussian Mixture Models) classification.

Paper ID: 2

Optimisation of the model for the numerical determination of the HRTF

Przemysław Plaskota (Wrocław University of Science and Technology)*

Corresponding author: **Przemysław Plaskota**, przemyslaw.plaskota@pwr.edu.pl

Recently, the issue of numerically determining the Head Related Transfer Function has been under constant consideration. The HRFT is the basis for creating individualised sound experiences in metaverse solutions.

This paper presents an analysis of different variants of the numerical model of an artificial head. Optimisation was carried out considering the upper limit frequency of the model, the size of the elements and their size distribution, the size and the enclosure properties of the head model.

The numerical model obtained as a result of the work is characterised by a short computation time with a sufficiently high upper limit frequency. The results obtained were compared with measurements of the real object, which confirmed the correctness of the designed model.

Paper ID: 3

Preliminary Study: Mobile Phone as a Phonocardiographic Signal Recorder

Michał Łuczyński (Wrocław University of Science and Technology)*

Corresponding author: **Michał Łuczyński**, michal.luczynski@pwr.edu.pl

The aim of this work is to analyze the possibility of using a mobile phone with a voice recorder function as a phonocardiographic signal recorder. Test measurements were carried out by placing the phone at various points on the chest. For one selected point, measurements were carried out for a group of about 100 people, using different models of mobile phones. Data on weight, height and age were collected through a survey. Participants of the study were also asked about potential problems related to the measurement.

Signal quality was assessed using qualitative parameters. It was checked how the selected methods of signal pre-processing (editing of recordings, filtering, noise reduction) affect the values of quality parameters. The obtained recordings were subjected to automatic signal classification.

The result of this work is an extended analysis of the use of mobile phones as electronic stethoscopes and an analysis of the usefulness of signals obtained using this measurement method.

The results of these studies are important for the field of medical diagnostics, especially in situations where access to traditional stethoscopes is limited. If mobile phones prove to be effective recorders of phonocardiographic signals, it will open new possibilities in the field of remote heart monitoring and telemedicine.

However, it should be noted that further research, including validation and comparison of results obtained with mobile phones with those obtained with traditional stethoscopes, is needed before this technology is introduced into clinical practice.

Paper ID: 4

Crowd noise spectra for the calculation of the speech transmission index for public address systems

Paweł Dziechciński (Politechnika Wrocławska)*

Corresponding author: **Paweł Dziechciński**, pawel.dziehcinski@pwr.edu.pl

Knowledge about interfering noise in the area of coverage is necessary for the correct design of a public address system. Acquiring this knowledge for existing buildings is possible, for example, by measurements. In the case of a non-existing or non-operating building, it is possible to obtain data on the basis of similar buildings. In practice, knowledge about interfering noise for design purposes is obtained from the literature, calculated, or using in-house experience. The sound levels of interfering noise can be obtained, for example, from BS 5389-1. It is more difficult to acquire knowledge of the interfering noise spectra, and as presented in the paper, the spectrum is also important for speech intelligibility. For example, for interfering noise with a sound level of 60 dB, in the free field, for large distances from the source, the value of the Speech Transmission Index for Public Address Systems (STIPA) for noise with a male speech spectrum can be as much as 0.15 greater than for noise with a pink noise spectrum. The paper attempts to systematise interference spectra occurring in public buildings where public address systems are most commonly used. As shown in the paper, the error in determining STIPA for appropriately selected normalised interfering noise spectra (speech for adequate vocal effort and white, pink and brown noise), relative to STIPA values for measurement-acquired noise spectra is relatively small. The main focus was on crowd noise, in buildings such as sports arenas and stadiums, waiting rooms, offices, restaurants, stores, airport terminals, etc., and interference on railway platforms. In the study, these analyses were performed by computer simulations using the STIPA statistical model.

Paper ID: 5

Lossy coding and bitrate effects on changes in formant frequencies in Japanese and English speech signals

Mateusz A Kucharski (Wrocław University of Science and Technology)*

Corresponding author: **Mateusz A Kucharski**, mateusz.kucharski@pwr.edu.pl

Since speaker recognition and verification became heavily used technology, both in professional applications like forensics and more everyday ones, the question arose: what factors can impact results of those processes? One thing that may be important with respect to this subject is lossy coding, as some of the information contained in an original file is lost in the coding process. In the era of globalization, not only native languages or languages of neighboring countries are of interest to researchers, but also those quite far, especially from Asia – the biggest exporter of goods and services to Europe. Those economic relationships are usually connected with the interchange of personnel, which further shortens geographical distance. The article presents the results that are a continuation of research on the behavior of Japanese language formants. Earlier research looked at changes to the trajectories of the first and second formants. This article presents the results of research on the third and fourth formants. The knowledge of these changes is indicated in the process of speaker identification in forensics using the spectrographic method. At the Department of Acoustics and Multimedia, Wrocław University of Science and Technology and in many centers around the world, the auditory-spectrographic method is used, which is a combination of the aural and spectrographic methods. In the spectrographic part, a person is identified on the basis of a comparison of the formants' trajectory.

Paper ID: 6

Acoustic model for the classification of Polish vowels

Karolina Maria Pondel-Sycz (Warsaw University of Technology)*

Corresponding author: **Karolina Maria Pondel-Sycz**, karolina.pondel.dokt@pw.edu.pl

The study explored the performance of vowel recognition using an acoustic model built on Audio Fingerprint techniques. The research compares the performance of Support Vector Machines (SVMs), Hidden Markov Models (HMMs), Artificial Neural Networks (ANNs) and K-Nearest Neighbors (k-NN) classifiers in the recognition of isolated and within-word vowels and investigates the importance of different types of acoustic speech features in this process. Temporal, spectral, cepstral, formant, LPC and perceptual features of speech were examined. Importance of features was tested using a random forest classifier. Vowel classification was tested at three confidence levels for feature importance: 90%, 95% and 99%. Two author databases consisting of a total of 1,200 samples from 20 speakers, recorded under household conditions, were used. The classifiers were evaluated by confusion matrix, accuracy, precision, sensitivity and F1 score. A segmentation of words into speech sounds was carried out using a tool based on BiLSTM recurrent neural networks and the BIC criterion. Three most important features were determined: power spectral density, spectral cut-off and Power-Normalised Cepstral Coefficients. In the isolated vowel recognition task, the SVM classifier was the most effective with a feature significance confidence level of 95% obtaining accuracy = 81%, precision = 81%, sensitivity = 81%, F1 score = 80%. In the task of recognising a vowel within a word, it was verified if the algorithm detected the presence of vowels in the correct segment and if it recognised the correct vowel within it. The best results were obtained by the k-NN classifier (statistical confidence level of feature importance of 99.9%). However, these results were low, correct recognition of the vowel in the word: A, E, U 20%, I, O: 7%, Y: 23%. This indicates strong influence of the neighbourhood of other speech sounds in speech on the acoustic model of vowels and their recognition.

Paper ID: 7

Objective Assessment of the Speech Signal Quality Broadcasted by Local Digital Radio in Selected Locations in Wrocław

Stefan Brachmański (Wrocław University of Science and Technology)*; Maurycy J. Kin (Wrocław University of Science and Technology); Natalia Rurzyńska (KFB Acoustics Sp. z o. o.)

Corresponding author: **Stefan Brachmański**, stefan.brachmanski@pwr.edu.pl

The development of digital radio, observed in recent years, and the advantages offered by this medium are resulting in the expansion of the audience. In order to ensure the proper quality of broadcasting, it is necessary to monitor this quality. The assessment based on listening tests is very expensive and organizationally inconvenient. The development of methods for objective evaluation of signals makes it possible to monitor the quality of transmitted content, without the need for troublesome procedures associated with subjective evaluation. The good correlation of subjective evaluation results and objective measurements in the transmission of perceptually encoded signals, reported in the literature, may allow for random quality monitoring. The authors decided to test the feasibility of using two objective evaluation methods to assess the quality of the speech signal transmitted on digital radio by comparing the results obtained with the result of subjective evaluation. The paper presents the results of objective measurements of speech quality transmitted via Digital Audio Broadcasting+ in Wrocław agglomeration. Measurements have been done in various city sites in order to determine the influence of the location on speech quality. The obtained results of the assessment performed by the use of two methods of testing: PESQ and POLQA, allowed to find a correlation between the objective and subjective results of quality evaluations. The method of objective testing may be used for monitoring the quality of signals in Digital Audio Broadcasting networks especially spoken broadcasts

Paper ID: 8

Analysis of asthma patients' auscultatory sounds.

Jędrzej Kociński (Department of Acoustics, Faculty of Physics, Dam Mickiewicz University, Poznań)*; **Honorata Hafke-Dys** (1) Department of Acoustics, Faculty of Physics, Dam Mickiewicz University, Poznań 2) StethoMe sp. z o.o.); **Tomasz Grzywalski** (WAVES Research Group, Department of Information Technology, Ghent University, Ghent, Belgium 2) StethoMe Sp. z o.o.); **Anna Pastusiak** (1) Department of Acoustics, Faculty of Physics, Dam Mickiewicz University, Poznań 2) StethoMe sp. z o.o.); **Adam Biniakowski** (StethoMe sp. z o.o.); **Krzysztof Szarzyński** (StethoMe sp. z o.o.)

Corresponding author: **Jędrzej Kociński**, jedrzej.kocinski@amu.edu.pl

Asthma is a global chronic disease that poses a significant burden on public health. The World Health Organization estimates that approximately 300 million people worldwide suffer from asthma, and this number is projected to increase by 100 million by 2025. Childhood asthma is the most prevalent chronic disease, affecting 10-12% of children worldwide and accounting for a significant portion of the childhood health burden. Despite its high prevalence, the current treatment outcomes for childhood asthma remain inadequate, and preventable deaths occur each year. Furthermore, diagnostic challenges contribute to both overdiagnosis and underdiagnosis of childhood asthma.

The current asthma diagnosis is primarily based on the subjective measurement of respiratory symptoms, which are reported by patients or their caregivers during routine clinical visits over an extended period of up to one year. However, this subjective measurement approach introduces a high degree of uncertainty into the input data, making accurate diagnosis challenging.

Objective analysis of respiratory sounds presents a solution for obtaining more precise and reliable diagnostic data. This study proposes an approach for the objective analysis of auscultatory signals in asthma patients. By implementing this approach, physicians can obtain more objective data for asthma diagnosis and improve treatment outcomes, ultimately reducing the burden of asthma on public health.

Paper ID: 10

Residual convolutional neural network for continuous identification of aircraft noise

Michał J Bukala (Politechnika Śląska)*; Artur Nowoświat (Politechnika Śląska); Andrzej Chyla (SVANTEK)

Corresponding author: **Michał J Bukala**, *michal.bukala@polsl.pl*

Continuous aircraft noise monitoring systems are the key to a strategic approach to noise management in the vicinity of airports and helipads. They support shaping the spatial distribution of the emitted noise, e.g. by providing data to optimize the use of approach and departure paths, the distribution of aircraft types during the day etc. in the annual perspective, taking into account alterations in the airport operating patterns and the fleet served.

In the single-operation scope noise monitoring systems allow for indicating anomalous aircraft movements which often become an issue from the perspective of a local community, and thus are of interest to airport authorities.

The latter class of problems requires a system to quickly, automatically and accurately identify whether the limit-exceeding noise event is caused by the aircraft operation. Due to the often delayed access to airport operation logs, the system should operate with minimal or no non-acoustic data. The paper proposes the architecture of a noise detection method, meeting the above requirements and attempts to assess its effectiveness.

Proposed approach involves using the residual convolutional neural network for solving the task. The network operates on 1/3 octave noise input data, returning the similarity of the input sound to the aircraft noise.

The accuracy of the proposed method determined for a single data frame using mixture of real-life measurements exceeds 95% for a frame length of at least 30 seconds.

The proposed method gives promising enough results that it can be implemented in a test environment on a larger scale. In parallel, further work is progressing, focusing mainly on improving the quality of training data and fine-tuning the hyperparameters of the network.

Paper ID: 13

Acoustic classification with the descriptor of the weighted standardized level difference $D_{nT,w}$ and of the weighted apparent sound reduction index $R'w$. Are the classes the same?

Reinhard O. Neubauer (IBN Bauphysik GmbH & Co. KG)*

Corresponding author: **Reinhard O. Neubauer**, dr.neubauer@ibn.de

Building regulations specifies technical requirements to sound insulation performance. This will be often done by using a single number rating like the weighted apparent sound reduction index $R'w$ or the weighted standardized level difference $D_{nT,w}$. A better description of the quality of sound insulation would be the formation of classes. If acoustic classes are provided, the question arises to what extent are $R'w$ and $D_{nT,w}$ the same. Can a sound insulation class be equal with both descriptors $R'w$ and $D_{nT,w}$? This paper compares the two parameters and presents the class formation of both descriptors.

Paper ID: 14

Experimental aeroacoustic studies of selected three types of helicoidal resonators

Wojciech Łapka (Poznań University of Technology); Piotr PJ Jakubowski (Maritime Advanced Research Centre)*

Corresponding author: **Piotr PJ Jakubowski**, piotr.jakubowski@cto.gda.pl

The paper presents experimental studies of selected three types of helicoidal resonators carried out on an aeroacoustic laboratory stand with the use of pink noise and a duct terminated with a reverberation chamber. The same ratio $s/d=1,976$ is considered for three numbers of helicoidal turns $n=0,671$, $n=0,695$ and $n=1.0$. The results of the acoustic attenuation performance depending on the air flow velocity were compared in relation to the numerical test carried out, with resulted in a decrease in resonance frequencies with an increase in the air flow velocity. The measurements were carried out with a high resolution of the FFT spectrum in order to illustrate the changes in the acoustic attenuation performance as accurately as possible. One-third octave bands of flow noise studies were also carried out.

Paper ID: 15

Evaluation of the impact of a leak on the sound transmission loss of a building partition using sound intensity measurements

Romuald Bolejko (Wroclaw University of Technology)*

Corresponding author: **Romuald Bolejko**, romuald.bolejko@pwr.edu.pl

Leaks in building partitions, e.g. at the point of their connection or in the form of poorly filled joints, can significantly affect the resultant sound transmission loss. For partitions in existing buildings with potential leaks, a leak identification method and, above all, a way of assessing the impact of such a leak on their parameters are needed. In this paper, a new method of evaluating the impact of leakage on the resultant sound transmission loss of the partition based on sound intensity distribution measurements was proposed. The tested building element is represented by two-element partition: a tight element and a leak of a certain area and sound insulation. The relationship between the sound transmission loss of a tight partition and the leak is determined on the basis of the measurement of the sound intensity distribution on the surface of the tested element with a leak. Once the relationship is defined, it is possible to predict the recovery of sound transmission loss of the partition as a result of removing the leak.

The paper presents the developed methodology and the results of its verification based on the measurement of sound insulation of a homogeneous partition, with and without leak, using the sound pressure method and the sound intensity method. Measurements were carried out in downscaled reverberation chambers with scale 1:4. A homogeneous MDF board was used with the leakage in the form of holes of a specific diameter. The measurement results were also compared to the values obtained by calculation using well-known Gomperts model of sound transmission loss of the partition with a leak. The measurements and calculations confirmed the possibility of determining the impact of leakage on the resultant sound insulation based only on the measurement of the sound intensity distribution on the surface of the tested partition.

Paper ID: 16

Control of spectral components in additive resynthesis as a means to alter sensation of consonance in chords

Marek Janusz Pluta (AGH University of Science and Technology)*

Corresponding author: **Marek Janusz Pluta**, pluta@agh.edu.pl

A prior study presented a possibility to impact the sensation of consonance by controlling spectral components of simultaneous pitches consisting a chord in sound synthesis using the additive method. It involves considering spectral components in all simultaneously sounding pitches consisting a chord. Components within the range of beating and roughness are modified to gradually strengthen or weaken both phenomena. So far, the idea and method had been implemented in a basic additive synthesizer producing simple, abstract, time-invariant timbres. The current study carries out the research further, and discusses problems of implementing aforementioned consonance-altering mechanism in a more complex additive synthesizer, applied to resynthesize sound of selected acoustic instruments. The study deals with natural independent evolution of spectral components, where consonance gradually varies with time. Moreover, it presents a solution to mitigate impact of the mechanism on a total signal level, caused by attenuation of selected components.

Paper ID: 17

Sound insulation – comparison of standard vs. real world situations

Michael Vorlaender (RWTH Aachen University)*

Corresponding author: **Michael Vorlaender**, mvo@akustik.rwth-aachen.de

Standardized sound insulation metrics are essential for testing of building elements and for field measurements in order to ensure comparability of data. When it comes to a real-world situation, however, the source and receiver positions and the source directivities might differ from those in the standard setting. An auralization framework based on ISO 12354-1 is briefly described. In an application of the framework, a study on the impact of specific source positions and orientations on the effective sound level difference is discussed in a few examples.

Paper ID: 18

Acoustic adaptation of ventilation system prototypes dedicated to individual classrooms

Artur Nowoświat (Politechnika Śląska)*; Rafał Żuchowski (Politechnika Śląska); Michał Marchacz (Politechnika Śląska); Marcelina Olechowska (Politechnika Śląska)

Corresponding author: **Artur Nowoświat**, artur.nowoswiat@polsl.pl

The prototypes of innovative ventilation systems dedicated to individual classrooms are designed to solve the problem of poor air quality in schools while reducing the need for the energy necessary for heating. At the same time, the working ventilation system must meet the acoustic requirements. These requirements specify the permissible value of the L_{Aeq} of the sound level = 40 dB as the average value of six measurement points. For this purpose, several studies have been carried out. First, a room was prepared that mimics a real-scale classroom with equipment and models of students. Calibration of such a room model was carried out by means of reverberation time measurements in octave bands of the frequencies 125 Hz, 250 Hz, 500 Hz, 1000 Hz, 2000 Hz, 4000 Hz. In the calibrated room, The prototypes of innovative ventilation prototypes were successively installed and the noise level in the room was tested. In the event of failure to meet the requirements, acoustic adaptations were made, and measurements were made again. The task was successful when the sound level at each measurement point and the average sound level did not exceed 40 dB.

Paper ID: 19

The influence of composite material manufacturing technology on the change of insulation from impact sounds

Daria Żuk (Uniwersytet Morski w Gdyni)*; Norbert Abramczyk (Uniwersytet Morski w Gdyni); Piotr PJ Jakubowski (Maritime Advanced Research Centre)

Corresponding author: **Daria Żuk**, d.zuk@wm.umg.edu.pl

The paper shows the influence of the composite material manufacturing technology on the change of the insulation parameter from impact sounds and the ability to dampen structural vibrations by modifying the structure of the composite material with the addition of rubber recyclate. Tests of acoustic insulation from impact sounds were carried out on a sandwich composite made on the basis of Synolite 1967-G-1 polyester resin and glass mat with a random arrangement of fibers and a weight of 350 g/m². As an additive modifying improving damping efficiency, rubber recyclate created in the process of disposal of car tires was used. The material was made using the vacuum infusion method. Composite materials were tested in three variants of the arrangement of recyclate in the produced composite in the form of 1, 2 and 3 sandwich layers. In the field of "in-situ" field tests, the reduction of the impact sound level by the ceiling with the tested plate made of composite material in relation to the ceiling without $\Delta L'$ plate was determined in accordance with PN-EN ISO 16283-2 and PN-EN ISO 717-2. The best insulation from impact sounds was obtained for a board made of material with 3 sandwich layers, which is $\Delta L' = 20.6$ dB. A decrease in the impact sound level of the board with 3 sandwich layers in relation to the composite board without the addition of recyclate was also determined, demonstrating the effect of rubber recyclate additives on the attenuation of structural sounds in the tested material. The use of rubber recyclate obtained in the process of disposal of car tires has an impact on improving environmental protection.

Paper ID: 20

Acoustic insulation tests of a multi-layer composite modified with rubber recyclate

Norbert Abramczyk (Uniwersytet Morski w Gdyni)*; Daria Żuk (Uniwersytet Morski w Gdyni); Piotr PJ Jakubowski (Maritime Advanced Research Centre)

Corresponding author: **Norbert Abramczyk**, n.abramczyk@wm.umg.edu.pl

The paper presents acoustic studies of a multilayer composite made on the basis of Synolite 1967-G-1 polyester resin and glass fabric with a three-way arrangement of $\pm 45^\circ$, Triaxial type and a weight of 860 g/m^2 . As an addition, rubber recyclate created in the process of disposal of car tires was used. The material was made using the vacuum infusion method. By vacuum lamination, composite materials were produced in the form of plates with the addition of rubber recyclate in four variants of the amount of recyclate used in the produced composite – 20%, 30%, 40% and 50%. Each variant contained 6 layers of fabric and five layers of rubber recyclate. The samples were tested in the vibroacoustic laboratory on a dedicated measuring station of the reverberation chamber assembly without lateral transmission, in which the specific acoustic insulation R was determined in accordance with PN-EN ISO 10140-2 and related standards, i.e. PN-EN ISO 10140-1, PN-EN ISO 10140-4, PN-EN ISO 10140-5 and PN EN ISO 717-1. All manufactured variants of the composite material with the addition of rubber recyclate were characterized by acoustic insulation in the range of $R_w = (32.5 \div 39.5) \text{ dB}$. High sound insulation parameters for tested panels up to 12 mm thick constitute a barrier to counteracting the spread of unwanted airborne noise. Combined with good mechanical properties such as tensile strength, toughness and hardness, they form the basis for the easy design of all shields in many industries. The use of rubber recyclate obtained in the process of disposal of car tires has a positive impact on improving environmental protection.

Paper ID: 22

Electrodynamic pick-up for electric string instruments

Edward R Reszke ("Ertec-Poland dr Edward Reszke")*; Andrzej B. Dobrucki (Wrocław University of Science and Technology)

Corresponding author: **Edward R Reszke**, ertec@wp.pl

The most important elements in electric musical string instruments are pick-ups. They convert vibration of strings into electric signal. Usually, two types of pick-ups are used: electromagnetic and piezoelectric. Electromagnetic pick-up, called also a pick-up with moving armature, converts vibration of string into an electric signal using change of magnetic flux in the magnetic circuit by the vibration of the string made of magnetic material. Vibrating string causes change of the air gap between the string (which is a moving armature) and rest of magnetic circuit. A variable electromotive force is generated in the stationary winding. In order for it to be proportional to the speed of vibration, polarization is needed, which is achieved by using a permanent magnet in the magnetic circuit. In a piezoelectric transducer, an electric current is generated due to the deformation of the piezoelectric material under the influence of a vibrating string. The subject of this paper is a stringed instrument with a electrodynamic transducer, which converts mechanical vibration of strings into an electromotive force which is produced between the ends of moving wire placed in the permanent magnetic field. This transducer is also called a transducer with moving wire. A wire (string) is made of a conductive material, but not necessarily a magnetic material. The principle of operation is similar to that of a ribbon microphone. The electromotive force induced at the ends of the string is very small and must be strongly amplified. It's a novel technique which is applicable in electric stringed instruments such as guitar, violin, viola, cello, double bass, and others. It has already been described in form of the patent application registered by Polish Patent Office and it is now designated to the further patent actions abroad based upon this priority document.

Paper ID: 23

Acoustic aspects of the modernization project of the Pomeranian Philharmonic in Bydgoszcz

Tadeusz Kamisiński (AGH University of Science and Technology)*

Corresponding author: **Tadeusz Kamisiński**, *kamisins@agh.edu.pl*

The comprehensive modernization of the Pomeranian Philharmonic, planned by the city of Bydgoszcz Ignacy Jan Paderewski will cover the existing part of the building with the well-known concert hall with recognized acoustics and the extension of the building with new rooms. The paper discusses selected acoustic and functional aspects of rooms in the context of acoustic parameters of interiors, construction and testing of acoustic structures and noise protection of rooms. These solutions fit into a very interesting and bold architectural design.

Paper ID: 24

Analytical modeling of the harmonic distortion caused by squeeze film damping in MEMS-based acoustic transducers

Anton Melnikov (Bosch Sensortec)*; Hermann A.G. Schenk (Bosch Sensortec); Franziska Wall (Fraunhofer IPMS)

Corresponding author: **Anton Melnikov**, anton.melnikov@bosch-sensortec.com

Miniaturized microelectromechanical system (MEMS) microspeakers are currently trending in the development of acoustic transducers. When a transducer is scaled down to fit on a microelectronic chip, its physics differ from the macroscopic world, and some common modeling assumptions become invalid. One of the effects observed in MEMS microspeakers is nonlinear squeeze film damping. Understanding this effect is crucial as non-linearities in the speaker can result in harmonic distortion, which is highly regulated in audio applications. In this study, we analyze the influence of squeeze film damping on harmonic distortion using a lumped parameter model of a MEMS microspeaker. This leads to a non-linear ordinary differential equation, and an approximate analytical solution for moderate non-linearities is obtained using homotopy. We present our solution strategy, including the resulting closed-form expression, and verify our findings against numerical solutions.

Paper ID: 25

Simulation of acoustic lens influence on wavefront shaping

Tomasz Nowak (Wrocław University of Science and Technology)*; Andrzej B. Dobrucki (Wrocław University of Science and Technology)

Corresponding author: **Tomasz Nowak**, t.nowak@pwr.edu.pl

The main objective of presented study is to examine the influence of an acoustic lens on shape of the wavefront. To conveniently illustrate the difference between acoustic pressure wave propagation with and without the lens, an isodynamic transducer was chosen as a source. This kind of loudspeaker generates flat wavefront as a result of approximately uniform distribution of speed and phase on the entire diaphragm. The designed lens consisted of a matrix of individual waveguides. Manipulation of size and position of output matrix in relation to input matrix allowed for achieving the desired waveguide length distribution. Differences in lengths of lens's channels resulted in wavefront delay distribution at the output matrix. A numerical model of transducer and waveguide matrix was created to evaluate the behaviour of acoustic pressure wave propagation through the designed lens. With stationary study, a spatial pressure distribution was calculated, in the near field and far field, in hemisphere in front of the lens as well as in hemisphere in front of just the transducer. The differences in wavefront shapes between the two cases were clearly visible in comparisons, confirming the expected pressure wave delay distribution of the lens. The resulting wavefront curvature was compared to the assumed one in theoretical design. Results of those comparisons proved the possibility of influencing the wavefront shape, by manipulating the output matrix with some caveats discussed in the paper. The data from numerical calculation of pressure propagation allowed for visualizing calculated sound pressure level distribution, adding the directivity evaluation to the comparisons.

Paper ID: 26

Infrasound and Well-being: A Study of Wind Turbine Impact

Paweł Małecki (AGH University of Science and Technology)*; Małgorzata Pawlaczyk-Łuszczynska (Instytut Medycyny Pracy im. prof. J. Nofera); Tadeusz Wszolek (Akademia Górniczo-Hutnicza w Krakowie); Bohdan Drzymala (SourceTech Business Process Outsourcing)

Corresponding author: **Paweł Małecki**, pawel.malecki@agh.edu.pl

Wind turbines serve as a distinctive source of noise, possessing unique attributes such as amplitude modulation, tonality, and components of infrasound and low frequency. This study explored how these sounds affect human well-being. A total of 129 subjects participated in the study, carrying out attention-focused tests and filling out surveys under three different conditions: normal background noise, artificially created low-frequency noise, and wind turbine-originated infrasound. The test results and the number of discomforts reported post-experiment did not significantly differ among the various conditions for both males and females. However, it was noted that the well-being before the study had a bearing on the complaints reported after the study.

Paper ID: 27

Experimental tests of selected sound-absorbing materials dedicated for a hydroacoustic measuring basin

Aleksander M. Schmidt (Politechnika Gdańska Wydział Elektroniki, Telekomunikacji i Informatyki Katedra Systemów Sonarowych)*; Lech Kilian (Gdańsk University of Technology Faculty of Electronics, Telecommunications and Informatics, Department of Sonar Systems); Jacek Marszał (Gdańsk University of Technology Faculty of Electronics, Telecommunications and Informatics, Department of Sonar Systems)

Corresponding author: **Aleksander M. Schmidt**, aleksander.schmidt@pg.edu.pl

Several scientific institutions from the Gdańsk community participate in the implementation of the grant from the Ministry of Education and Science "Concept of building metrological infrastructure in the area of underwater acoustics at the Central Office of Measures". In practice, the concept includes, among other things, the design of two measurement basins: a large-size one for measurements in the range of possibly low ultrasound frequencies (from several dozen kHz) and a small-size one (from several hundred kHz). One of the basic conditions for the proper implementation of measurements is to obtain minimum sound reflections from the water surface, walls and bottom in basins. This is possible by covering these surfaces with sound-dispersing materials or so-called acoustic absorbers. The frequency characteristics of these properties are decisive here, but also the price, ease of assembly, cleaning and slow aging. The article presents the results of the measurements of the signal attenuation after passing through the tested materials, the values of the levels of attenuated echoes and the calculated of the absorption coefficients of currently available and promising layers of "synthetic grass" with different lengths of blades, plates made of various plastics and, for comparison, curtains made of dispersing brushes, damping the measuring basin of the Department of Sonar Systems for several decades. The obtained characteristics were compared with those presented by the manufacturer of commercial absorbent panels.

Paper ID: 28

Questionnaires and Acoustic Measurements in Longyearbyen Area, Svalbard

Jerzy Wiciak (AGH University of Krakow)*; Dorota Młynarczyk (AGH University of Krakow); Paweł Małecki (AGH University of Science and Technology); Janusz Piechowicz (AGH University of Science and Technology)

Corresponding author: **Jerzy Wiciak**, wiciak@agh.edu.pl

Svalbard is a Norwegian province in the Arctic, covering the Svalbard archipelago and islands within 71°–81° N and 10°–35° E. The largest town on the island of Spitsbergen is Longyearbyen, with a population of around 2,100. It is the main centre of administration with the governor's office, and there are many public buildings, a housing estate, a harbour and an airport. This paper presents selected results from a survey on the quality of environment and soundscape of Spitsbergen. The results of acoustic measurements of selected sites near Longyearbyen are also presented. Based on the responses, three groups of tourist activity were identified: (1) Longyearbyen activity: a round trip of town, visit to the museum, mine no. 3 and UNIS visits, (2) Snowmobile trips: to Barenstburg, East Cost and Elveneset, (3) Nature hikes: trips to the summits of the Sarkofagen and Trollsteinen peak, hiking on the Larsbreen, Longyearbreen and Tellbreen glaciers and visits to glacier caves. Of these sites, acoustic analyses (SPL – time and frequency characteristics) were conducted at the following locations: Longyeardalen: Unis area and city centre, Adventalen: dog sleds and snowmobiles rides, Nature hike: to Sarkofagen peak and caves in Larsbreen and Longyearbreen glaciers.

Paper ID: 30

Contrast-enhanced magneto-motive ultrasound imaging of sentinel lymph nodes

Katarzyna Kaczmarek (University of Silesia in Katowice)*

Corresponding author: **Katarzyna Kaczmarek**, katarzyna.kaczmarek@us.edu.pl

Contrast-enhanced magneto-motive ultrasound imaging of sentinel lymph nodes

K. Kaczmarek*¹, S. Sjöstrand¹, M. Bacou², A. Thomson³, T. Jansen⁴, S. Moug⁵, S. Farrington², C. M. Moran³, H. Mulvana¹

*Institute of Chemistry, University of Silesia in Katowice, Poland

¹ Department of Biomedical Engineering, University of Strathclyde, Glasgow, UK

² Institute of Genetics and Cancer, University of Edinburgh, Edinburgh, UK

³ Centre for Cardiovascular Science, University of Edinburgh, Edinburgh, UK

⁴ Department of Clinical Sciences Biomedical Engineering, Lund University, Lund, Sweden

⁵ Department of Surgery, Royal Alexandra Hospital, Scotland, UK

A very crucial step in cancer staging is the process of identification of cancerous lymph nodes. The absence of metastases in the sentinel node determines the lower probability of metastasis in other draining nodes and distant organs. Commonly used in clinical practice methods, such as blue dye-, isotope-, and green fluorescence- staining, are lacking accuracy.

As an alternative to generally used sentinel lymph node identification methods, Contrast-Enhanced Magneto-Motive Ultrasound (CE-MMUS) has been proposed. CE-MMUS uses magnetic microbubbles (microbubbles with attached magnetic nanoparticles) as contrast agents. Subsequently, a low-frequency alternating magnetic field induces oscillations of magnetic microbubbles to generate tissue-laden movement. The tissue-laden movement caused by magnetic microbubbles is tracked and recorded with a phase and frequency tracking algorithm.

Results showed that the functionalization of microbubbles with magnetic nanoparticles does not negatively affect their applicability as contrast agents, and their presence in the sentinel lymph node visibly increased its echogenicity. Derived with the tracking algorithm tissue displacement increased after the addition of magnetic microbubbles compared to displacement caused by magnetic nanoparticles only. Therefore, the CE-MMUS improved lymph node identification. Experiments were conducted on mice models in vivo.

This work was supported by CRUK-grant numbers A23333/24730.

Paper ID: 31

Noise Testing of Multi-disc Fan

Kamil Wójciak (Instytut Energetyki)*; Patryk Gaj (Instytut Energetyki); Joanna Kopania (Instytut Energetyki)

Corresponding author: **Kamil Wójciak**, kamil.wojciak@itc.edu.pl

The impeller of a multi-disc fan was made of rotating smooth discs spaced close together. The concept of such machine came from Nikola Tesla in 1909. The fluid, based on the principle of friction against the rotating surfaces of the discs, flows outwards from the disc pack into an outlet. According to the literature, such a design is characterized by low noise emissions. Based on calculations, a prototype of a multi-disc fan was designed and then manufactured. Tests were carried out for the sound power level emitted from the fan's outlet. The examination was performed in a reverberation chamber according to ISO 3741:2010 standard. The noise source was visualized using an acoustic camera. The aerodynamic characteristics were also determined experimentally according to ISO 5801:2017 standard. The acoustic and aerodynamic characteristics of the multi-disc fan were determined.

Paper ID: 32

Sound power level as a means of effectiveness of Distributed Mode Loudspeakers

Karol Czesak (Akademia Górniczo - Hutnicza im. Stanisława Staszica w Krakowie)*; Piotr Kleczkowski (AGH University of Science and Technology)

Corresponding author: **Karol Czesak**, *charles35.41@gmail.com*

Distributed Mode Loudspeakers (DMLs) are characterized by properties, which make them significantly different from – commonly used – conventional electrodynamic loudspeaker with a piston-like diaphragm. Such differences occur due to the design assumptions of the DML, which are totally differing from design principles of conventional loudspeakers. The vibrations of DML consist of bending waves traveling across the rectangular surface of the loudspeaker. That is the cause, why transducers of this type present frequency characteristics with sharp local minima occurring at various frequencies, depending on the angle between the loudspeaker's surface and a measurement microphone. Because of such a property DML produce an acoustic field which is diffusive in the proximity of the loudspeaker. Also, the directivity characteristics of the DML are differing from those related to piston-like loudspeakers. The previous works of these authors have shown that the strongest radiation did not occur at the axis of the transducer, which leads to a conclusion that the Sound Pressure Level measured on the axis of the loudspeaker ought not be conceived as the reference level when normalizing measurement results and calculating directivity specifications.

In this work, a series of sound pressure level measurements of DML in a reverberation chamber has been carried out, which were compared with analogous ones, carried out for a conventional electrodynamic loudspeaker. In further steps – sound power level, according to ISO 3741:2010 standard was determined from the results of conducted measurements for both types of transducers. The sound power level was calculated in 1/3 octave bands, for the filtered pink noise excitation of constant amplitude. It may be concluded, that the sound power level obtained with these two different types of loudspeakers is not significantly differing between each other, despite of various operating principles of transducers.

Paper ID: 33

Research in the use of metamaterial sound-absorbing structures in electroacoustics

Bartłomiej Chojnacki (AGH University of Science and Technology)*; Aleksandra Chojak (AGH Akademia Górniczo-Hutnicza); Jan Pawlik (AGH University of Science and Technology); Wojciech Binek (AGH University of Science and Technology); Julia Idczak (AGH University of Science and Technology)

Corresponding author: **Bartłomiej Chojnacki**, bchojnacki@agh.edu.pl

The metamaterial structures in sound absorbers' role have increased in popularity in many acoustic applications. However, electroacoustics's most popular absorber type is still porous material such as polyester fibers or acoustic foam. This paper will present the recent finding on the possibility of application for metamaterial acoustic absorbers dedicated to selected features in loudspeaker enclosures, such as standing wave attenuation or absorption of diaphragm backpropagation. The selected applications of metamaterial optimized structure will be demonstrated through numerical simulation and experimental measurements. The optimized structures for the selected application were modeled using COMSOL Multiphysics FEM modeling and Transfer Matrix Method calculation. The selected aspects of sample preparation produced in the 3D printing technique with different technologies of printing will be discussed, as well as the required postprocessing for this type of prototyping technique. We have used the most common rapid prototyping methods, such as FDM, DLP, and SLS, with different mechanical modifications and postprocessing to best match the modeling results in measurements on the impedance tube. The summary will provide feedback on the current stage of metamaterial structures applications in electroacoustics and difficulties in this research topic.

The project was funded and supported by the Polish Government, National Centre of Research and Development, agreement no. LIDER/11/0065/L-12/20/NCBR/2021.

Paper ID: 34

Investigation of tribological interactions influence on dynamics of optimal surgical robot with DC motor and PID controller taking into account inputs from in vitro experiments on cardiovascular tissue

Grzegorz Ilewicz (Warsaw University of Technology)*

Corresponding author: **Grzegorz Ilewicz**, grzegorz.ilewicz@pw.edu.pl

Tribological interactions are one of the basic reactions affecting the course of the drive torque in surgical robot joints. It is interesting to test out what is the impact of friction on its dynamics because it gives the possibility to effective control. Inputs from two in vitro experiments on cardiovascular tissue were added to optimization model which include such important physical phenomena as: natural vibrations, linear buckling and history of the deformation. It was assumed that the accuracy of positioning and repeatability of a surgical robot with a serial chain is influenced by such criteria as: first natural frequency, buckling coefficient, mass, dynamic safety factor during transient states and displacement of an end of the effector under the impact of emerging loads. A vector objective function for these four criteria was determined and its optimum with the usage of finite element method, Pareto fronts and the genetic algorithm NSGA-II was specified too. For the optimal obtained geometry, a model of dynamics of driving torques was constructed by using the block diagram method, taking into the account the inertia tensors and the locations of masses centers. The electromechanical DC motor model was added to each joint. PID regulator models were also added to them and step responses with optimal indicators of the regulation quality was received using gradient descent method. For a specific mechatronic system of the surgical robot, dynamic friction model was formulated based on the Lund-Grenoble model equation including the deformation of the cooperating plastic and elastic surfaces, and including the Stribeck effect.

Paper ID: 35

Assessment of acoustic quality of residential buildings in Poland - case study

Elżbieta Nowicka (Instytut Techniki Budowlanej)*

Corresponding author: **Elżbieta Nowicka**, *e.nowicka@itb.pl*

The requirements of people in relation acoustic comfort are very diverse. They depend on many factors. With regard to residential buildings notion of "satisfactory acoustic conditions" must take into account the need to provide a sense of intimacy, peace and security. Taking care of the appropriate acoustic quality of buildings, should result from compliance with applicable laws and be the responsibility of all participants in the construction process.

The article discusses the acoustic classification of residential buildings with a better acoustic quality, introduced in Poland in 2017. Also the overall legislative problem will be discussed.

Paper ID: 36

Assessment of the impact of road traffic noise based on post-realization analysis of a project

Rafał Żuchowski (Politechnika Śląska)*; Artur Nowoświat (Politechnika Śląska)

Corresponding author: **Rafał Żuchowski**, rafal.zuchowski@polsl.pl

The article presents the issue of post-implementation analysis of the road in terms of noise generated by road traffic, which affects the quality of life of residents and requires effective remedial actions. The post-implementation analysis allows for the assessment of the actual effects of road noise, the identification of areas requiring protection against noise and the monitoring of the effectiveness of the applied noise solutions based on field studies. It presents factors influencing the acoustic climate, such as traffic intensity, type of vehicles, road surface and applied acoustic protection. Presented is the current land development, such as the location of the road, its infrastructure and surroundings in the form of data obtained on the basis of the conducted terrain scanning. The conducted analysis of the measurement results was the basis for additional tests of the acoustic parameters of the existing acoustic screens. In addition, computer simulations were carried out, which allowed the assessment of the current acoustic climate along the entire length of the road and were the basis for developing a repair program to the extent required.

Paper ID: 37

Aeroacoustic parameters of the ceiling swirl diffuser with prototype adjustable-blades

Joanna Maria Kopania (Lodz University of Technology)*; Grzegorz Bogusławski (Lodz University of Technology); Patryk Gaj (Instytut Energetyki); Kamil Wójciak (Instytut Energetyki)

Corresponding author: **Joanna Maria Kopania**, joanna.kopania@p.lodz.pl

For the major part of our lives we are in the indoor air spend time in artificial climates such as work/home environments and transport vehicles. So, clean air in a room is an essential component for a healthy indoor environment. Ventilation systems are responsible for exchanging air in rooms. Devices controlling the room ventilation are called ATD's (air terminal devices) - a general term used to describe supply, exhaust or transfer diffusers and grilles. The ceiling swirl air diffusers are mechanical devices designed to control the characteristics of fluid at the entrance to a thermodynamic open system. These units in HVAC systems are important because they create a swirl to supply air to rooms where people are and allow mixing flow ventilation in the comfort zone, but also they are the source of the noise. In this work, an aeroacoustic study of ceiling swirl diffusers with prototype manually adjustable air control blades in two positions, fully opened and by 45 angles, was performed. The objects were installed on the plenum box with a side entry without the damper. The prototype blades using the 3D printer were used to find the one with lower noise parameters which are set out by measuring according to ISO 5135.

Paper ID: 38

First-order ambisonics microphone with MEMS and condenser capsules

Marcin Lewandowski (Warsaw University of Technology)*; Aleksander Augustyniak (Warsaw University of Technology)

Corresponding author: **Marcin Lewandowski**, marcin.lewandowski@pw.edu.pl

Technologies that produce and deliver immersive VR content are still growing. Ambisonic microphones are available in various types, from the FOA (first-order ambisonics, e.g., Sennheiser AMBEO VR Mic) to HOA (up to fourth-order ambisonics, e.g., MH Acoustics Eigenmike). They are designed with different capsules, from low-cost electret transducers, MEMS (Zylia ZM-1) to high-grade condenser capsules (NEVATON VR). This paper presents two designs of a low-cost FOA microphone based on low-noise MEMS (Infineon IM69D130) and electret capsules (JLI-2590A) in an identical tetrahedral arrangement. This paper details the design, fabrication, and testing of two FOA microphones, including their frequency and directivity response and subjective evaluation compared to commercially available solutions. This study aims to indicate whether the microphone capsule's type affects the recorded sound field's quality and its significance.

Paper ID: 39

Azimuth and elevation errors in binaural reproduction of ambisonic sound.

Agnieszka Pietrzak (Politechnika Warszawska)*

Corresponding author: **Agnieszka Pietrzak**, A.Pietrzak@ire.pw.edu.pl

Binaural decoding of an ambisonic sound is reproducing the information about a soundfield over headphones. It is done based on the spherical harmonics representation of the spatial sound and on the use of Head Related Transfer Function (HRTF). Inaccuracies in the decoding process, which can be caused for example by using non-personalized HRTF, may lead to difficulties in localizing the sound source by the listener. Especially in the elevation plane, localization errors can be significant. In this study, listening tests were conducted in order compare azimuth and elevation errors for different binaural decoders. It is discussed how azimuth and elevation errors vary depending on the type of the binaural decoder used, for 1st and 3rd order ambisonic recordings of pink noise bursts.

Paper ID: 40

Thermodynamic properties of 1-allyl-3-methylimidazolium dicyanamide and 1-vinyl-3-methylimidazolium bis(trifluoromethylsulfonyl)imide

Lukasz Scheller (University of Silesia in Katowice)*; Krzysztof Cwynar (University of Silesia in Katowice); Marzena H. Dzida (University of Silesia in Katowice)

Corresponding author: **Lukasz Scheller**, lukasz.scheller@us.edu.pl

Ionic liquids (ILs) have emerged as promising alternatives to traditional organic solvents due to their unique properties, such as low volatility, high thermal stability, and remarkable tunability. Understanding the thermodynamic properties of ILs is crucial for their application in various fields, including energy storage, separation processes, and catalysis. In this study, we experimentally investigate the thermodynamic properties of two ILs, namely 1-allyl-3-methylimidazolium dicyanamide ([AMim][DCA]) and 1-vinyl-3-methylimidazolium bis(trifluoromethylsulfonyl)imide ([VMim][NTf2]), which have not been previously studied.

The speed of sound and isobaric heat capacity were measured in the temperature range from 293.15 to 323.15 K at atmospheric pressure. The density was measured in the temperature range from 278.15 to 363.15 K at ambient pressure. From the experimental data the related thermodynamic properties were calculated, i.e. isentropic and isothermal compressibility coefficients as well as the isobaric thermal expansion coefficients.

The results reveal that [AMim][DCA] exhibits higher values of speed of sound and isobaric heat capacity compared to [VMim][NTf2]. On the other hand, [VMim][NTf2] demonstrates higher density values and calculated coefficients compared to [AMim][DCA]. It was found that for that for [AMim][DCA] the temperature dependence of the isobaric coefficient of thermal expansion is stronger and negative – contrary to [VMim][NTf2], where this dependence is smaller and positive.

The data obtained in this study contribute to the development of reliable thermodynamic databases for ILs and a comprehensive understanding of their thermodynamic properties. The acquired knowledge enhances our understanding of IL behavior and facilitates the advancement of IL-based technologies.

This work was financially supported by the National Science Centre (Poland) Grant No. 2021/41/B/ST5/00892 in the framework of OPUS program.

Paper ID: 41

Comparison of the acoustic parameters of the commercial ceiling swirl diffusers with the prototype model

Grzegorz Bogusławski (Lodz University of Technology)*; Joanna Maria Kopania (Lodz University of Technology); Patryk Gaj (Instytut Energetyki); Kamil Wójciak (Instytut Energetyki)

Corresponding author: **Grzegorz Bogusławski**, grzegorz.boguslawski@p.lodz.pl

Understanding the behaviour of the airflow in ventilated rooms is essential for architects in order to provide the most efficient ventilation system and also for users of the rooms. In mechanical ventilation, it is necessary to control air quality in the human-occupied zone and this can be achieved by air diffusers of different kinds also called ATD's (air terminal devices) - a general term used to describe supply, exhaust or transfer diffusers and grilles. These units in ventilation systems are important because they create a swirl to supply air to rooms where people are and allow mixing flow ventilation in the comfort zone. But inside buildings fitted with air-conditioning systems, the majority of the noise comes from the air, i.e. caused by the movement and distribution of air between ducts and from the ducts into different areas through vents, diffusers and return grilles. In this work, an aeroacoustic study of four commercial adjustable-blade ceiling swirl diffusers and compare with prototype one was performed. Two positions of adjustable-blade, fully opened and by 45 angles, were performed. The objects were installed on the standard plenum box with a side entry without the regulation damper. The prototype blade was printed by the 3D printer. The aeroacoustics parameters were set out according to ISO 5135 in the reverberation room.

Paper ID: 42

Molecular structure and thermophysical properties of ionanofluids

Marzena H. Dzida (University of Silesia in Katowice)*

Corresponding author: **Marzena H. Dzida**, marzena.dzida@us.edu.pl

Investigated ionanofluids are hybrid systems composed of multi-walled carbon nanotubes dispersed in ionic liquids by ultrasonication method. They exhibit a range of desirable properties, including improved thermal conductivity, nonflammability as well as high chemical and thermal stability, making them efficient and safe heat transfer media. In particular, a remarkable increase in thermal conductivity was observed for ionanofluids based on C-sp² rich, long, crystalline multi-walled carbon nanotubes. The structural, cryo-transmission electron microscopic studies revealed the existence of subzipping effect of long multi-walled carbon nanotube networks in ionic liquids as a result of interactions between two neighboring nanotubes which fragmentarily coalescent by the ionic liquid nanolayers, i.e. intertube zipping together with locally unzipped individual pairs of nanotubes and/or longitudinally unzipped nanotubes. The energy of interactions between the carbon nanotube walls and ionic liquids, obtained from the molecular dynamics simulations, indicated that the formation of carbon nanotube networks, separated by a layer of ions, was thermodynamically favorable. Additionally, the correlation between the ID/IG and ID/I2D integrated intensity ratios in the Raman spectra suggested the formation of new covalent bonds between the ultrasonically induced broken nanotubes and the most likely cation. Consequently, the molecular perfection of the multi-walled carbon nanotube structure, along with its supramolecular arrangement and interactions with ionic liquid, significantly contribute to the extraordinary enhancement in thermal conductivity and optimal rheological characteristics.

This work was financially supported by the National Science Centre (Poland) Grant No. 2017/27/B/ST4/02748.

Paper ID: 43

Acoustic metamaterial design for levelling the impact of double-wall resonance on sound insulation

**Aleksandra Klimek (Wrocław University of Science and Technology)*; Andrzej B. Dobrucki
(Wrocław University of Science and Technology)**

Corresponding author: **Aleksandra Klimek**, aleksandra.klimek@pwr.edu.pl

This paper presents two solutions employing locally resonant metamaterial to level the mass-air-mass resonance impact on the sound insulation. The first operates on the cantilever beam resonance, and the second uses masses vibrating in flexural mode cut out from the additional panel. Both structures are mounted between two lightweight, honeycomb cardboard panels with a double-wall resonance of 420 Hz. Solutions were analysed numerically for their vibration and acoustic properties and measured in the reverberation chamber, resulting in information about the dispersion curve, effective dynamic mass, and sound insulation. The analytical results of Sound Transmission Loss (STL) and the experimental measurements of diffused-field Sound Reduction Index (SRI) proved the existence of sound-insulation enhancement. The local rise in SRI resulted in an increase of broadband Weighted SRI up to 5 dB.

Paper ID: 45

The influence of diffusing elements arrangement in a reverberation room on the results of airborne sound insulation measurements

Dominik Mleczko (AGH University of Science and Technology)*

Corresponding author: **Dominik Mleczko**, dmleczko@agh.edu.pl

The primary issue in evaluating airborne sound insulation lies in quantifying the sound energy emitted by the barrier. This is typically accomplished by measuring sound pressure levels and acoustic absorption within the receiving chamber. When significant fluctuations in sound pressure levels occur within a reverberation room, it indicates the presence of standing waves, necessitating the incorporation of diffusing elements. ISO 10140 has established specific thresholds that dictate the inclusion of reverberation time for frequencies equal to or surpassing 100 Hz. Nevertheless, there are instances, particularly in spacious rooms, where acquiring the requisite parameters becomes arduous and, at times, unfeasible. Under such circumstances, it becomes imperative to ascertain whether the measured sound insulation is contingent upon the reverberation time.

The presentation presents the measurement results of various diffusing elements configurations in a reverberation room. These diffusers aim to improve the uniformity of the acoustic field in terms of acoustic pressure and reverberation time. Therefore, the focus was on these two parameters. The ultimate goal was to assess the impact of changes in the arrangement of diffusers on the results of sound insulation measurements.

Paper ID: 46

The potential of liquid marbles and Pickering droplets as templates for colloidal capsules

Rafał Bielas (Faculty of Physics Adam Mickiewicz University in Poznań)*; Tomasz Kubiak (Faculty of Physics Adam Mickiewicz University in Poznań); Arkadiusz Józefczak (Adam Mickiewicz University in Poznań)

Corresponding author: **Rafał Bielas**, rafal.bielas@amu.edu.pl

One of the challenges in biomedical applications is the efficient protection of active substances (e.g., drug molecules) and precise delivery to the site of interest when a patient is under treatment or medical diagnostics. Capsules of rigid and dense shells can efficiently preserve the active substances. They can be fabricated from droplets coated with solid particles suspended in a carrier liquid (known as Pickering droplets). Another potential strategy is using so-called liquid marbles, which are droplets covered with particles but suspended in the air.

In the presentation, I will discuss the production of Pickering droplets and liquid marbles based on magnetic fluids. When exposed to a high-frequency alternating magnetic field, these droplets provide the basis for capsule formation. In the tested systems, polymer micro-particles constituting a shell around the droplets change their properties when influenced by generated heat in magnetic hyperthermia. Then, droplets formed in this way can be manipulated using a constant (DC) magnetic field and filled with an active substance, such as an antibiotic suspension. The results from our research will be supplemented with examples from the literature demonstrating the potential of droplets in the transport and release of active substances triggered by, among others, high-intensity ultrasound.

The presentation will also provide further possibilities in this area, including the control of droplet manipulation processes using ultrasound techniques and the active substance release from the droplets by ultrasound and controlled by electron paramagnetic resonance (EPR) techniques.

Paper ID: 47

Experimental validation of the asymmetric PZT optimal shape in the active vibration reduction of triangular plates

Romuald Kuras (Rzeszow University of Technology)*; Sebastian Hajder (Rzeszow University of Technology)

Corresponding author: **Romuald Kuras**, r.kuras@prz.edu.pl

In the active vibration reduction of two-dimensional structures, piezoelectric actuators of regular shapes, e.g. rectangular, circular, are commonly used. However, the shape of the transducers can be irregular, asymmetric (a-PZT), and its geometry can be an object for optimization. The paper presents an experimental validation of the application of optimal shaped a-PZT in the active reduction of triangular plate vibrations. Optimization was based on the criterion of the maximum bending moment. This means that the center of a-PZT is located at the point where the bending moment of the plate has reached its absolute maximum. The isosceles right triangular plate with simply supported edges was chosen as the research object. The research confirms the validity of the criterion used for optimization and may be an introduction to considering the use of optimal a-PZT in the active reduction of vibrations for more complex structures.

Paper ID: 48

Effect of phase modification of sound components on spatial impression in 2 and 3-component signals

Kamil Zimny (AGH University of Technology)*

Corresponding author: **Kamil Zimny**, kzimny@agh.edu.pl

Spatial perception of sounds is one of the fundamental properties of the auditory system, allowing for the localization of sound sources in space or the evaluation of room size. However, the mechanisms responsible for this phenomenon have not been fully understood and described yet. Research in this area indicates the existence of mechanisms in the higher levels of the auditory system that are responsible for creating the impression of spatiality. On the other hand, other studies have shown that the auditory system is sensitive to phase coherence between the components of complex signals, suggesting a relationship between these phenomena. Preliminary informal listening tests suggested that continuous phase shifts introduced into components of complex sounds evoke an impression of spatiality of these sounds.

The subject of this paper is the investigation of the influence of phase modifications on the perception of sound spatiality and the presentation of its results. Harmonic signals composed of 2 or 3 pure tones at specific fundamental frequencies were used in the study. The signal components were then phase-modified using specially designed algorithms and various parameters of phase change. The listening test involved a dozen participants, mostly students without specialized listening training, who were asked to compare the spatial impressions of sounds with phase modifications to those without them. The research was conducted in an audiometric cabin using headphones.

Paper ID: 49

Test stand for study of reverberating plates with adjustable features

Adam Korytowski (Akademia Górniczo-Hutnicza im. Stanisława Staszica w Krakowie)*; Wojciech Wronka (AGH University of Science and Technology)

Corresponding author: **Adam Korytowski**, adamkor@agh.edu.pl

Vibrations of plates can be used for synthesis of artificial reverberation, which is one of the most important signal processors in audio engineering. This paper describes a process of creating a test stand for measurements of reverberating plates. The stand was assumed to have possibilities to modify the output reverberation signal in perceptually significant way by affecting the plate vibrations. The paper contains description of mechanical and signal parts of the stand and their way of working as well as how they can be used in order to achieve differences in the output reverberation signal. The test stand will allow to examine how exactly affecting the vibrating plate will affect features of the reverberation signal.

Paper ID: 50

The impact of infrasound on the level of activation

Cezary Kasprzak (AGH)*

Corresponding author: **Cezary Kasprzak**, cekasp@agh.edu.pl

The present study provides a comprehensive analysis of research data elucidating the impact of infrasound on human activation levels. The levels of activation were quantified using the Activation-Deactivation Adjective Check List a widely recognized self-assessment questionnaire. Experimental studies were conducted in two independent research scenarios: the experimental study and the control study. The research procedures were uniform, differing only in the acoustic stimulus applied. In the experimental study, an acoustic stimulus with a frequency of $f = 13$ Hz and a sound pressure level of $SPL = 105$ dB (Lin) was employed. Statistically significant changes in activation level were obtained.

Paper ID: 51

Reconstruction of source components from hydroacoustic time series

Andreas Galka (Bundeswehr Technical Center for Ships and Naval Weapons, Maritime Technology and Research (WTD 71))*

Corresponding author: **Andreas Galka**, andreasgalka@bundeswehr.org

Hydroacoustic time series may contain mixtures of source components originating from natural or artificial sources. We demonstrate that reconstruction of these components can be accomplished by employing the methodology of parametric time series analysis. The core element of the proposed approach is the estimation of models for the prediction of the given time series, such as autoregressive moving-average models or state space models. These models can be generalised for non-stationary situations, such as gradual fading of sources or time-dependent frequencies, e.g., due to Doppler effects. Estimation of states and model parameters is implemented by Kalman filtering and numerical maximisation of the innovation likelihood. As a result of the proposed approach, source components can be detected and reconstructed, also in presence of strong background noise; this is important for the analysis of the hydroacoustic signature of ships. In some cases, additional information regarding the sources can be obtained, such as velocity and distance, or rotation rate of the propeller. As an additional benefit, parametric estimates of the power spectrum can be computed, which have attractive properties, as compared to classical methods for spectral analysis.

Paper ID: 52

A Tool for Designing Water Tanks for Measuring Hydroacoustic Transducers

Roman Salamon (Gdansk University of Technology, Faculty of Electronics, Telecommunications and Informatics, Department of Sonar Systems); Jacek Marszal (Gdansk University of Technology, Faculty of Electronics, Telecommunications and Informatics, Department of Sonar Systems)*; Iwona Kochańska (Politechnika Gdanska)

Corresponding author: **Jacek Marszal**, jacek.marszal@eti.pg.edu.pl

Special water tanks are commonly used to measure the parameters of underwater acoustic systems. They must meet specific requirements, the fulfilment of which ensures very small but acceptable measurement errors. These requirements define the size of the tank and its shape as well as the strong damping of reflected waves. At the design stage, it is necessary to determine the impact of the tank structure on the measurement errors and to adapt it to the expected measurement methodology. The article presents a mathematical tool for designing such water tanks using the impulse response method. Contrary to the use of this method in architectural design, the presented method is here used to determine the measurement signals emitted by ultrasonic transmitting transducers and received by receiving transducers (hydrophones). The relationships are given between the parameters of the pulse response and the design parameters of the tank and the measurement system, as well as its transfer functions and sample measurement signals.

Paper ID: 53

Impact of changes in the shape of sensor part of sensor-actuator hybrid on its effectiveness in plates' vibroacoustic reduction

Roman Trojanowski (AGH University of Krakow); Jerzy Wiciak (AGH University of Krakow)*

Corresponding author: **Jerzy Wiciak**, wiciak@agh.edu.pl

This work is a continuation of authors previous works on modelling a piezo electric sensor-actuator hybrid. For these models a change in sensor shape will be introduced to determine how it impacts the results. In order to preserve continuity with previous and future work a steel plate with 2 piezo elements and a half sphere of air was modelled using ANSYS software. One was used to excite plate's vibration, the other one for the purpose of vibration reduction. The first piezo element is a standard square based piezoactuator which will be used to excite the plates' vibrations. The second one can be either a standard square based piezoactuator or a sensor-actuator hybrid with a square based actuator part and either disc or square based sensor part with different sizes. Harmonic analyses were performed for the 1st, 2nd, 4th and 5th mode shapes using internal ANSYS optimization functions with the goal function being the minimization of displacement vector sum of a number of nodes with 3 possible cases. 1st case – all nodes making the back of the plate used as sensor, 2nd case – “virtual” sensor placed on diagonal of the plate, 3rd case – sensor placed where the sensor part of a hybrid is placed. Results presented obtained reduction for the plate and the differences between standard actuators and proposed sensor-actuator hybrids.

Paper ID: 54

Sound Propagation Experiments in the Western Baltic Sea

Jan Abshagen (WTD 71)*; Christian Haak (WTD 71)

Corresponding author: **Jan Abshagen**, janabshagen@bundeswehr.org

Sound propagation in the Baltic Sea exhibits special characteristics due to complex oceanographic conditions in this area. In the last two decades experiments on sound propagation in the Baltic sea have been predominately performed east of the Darss Sill. Compared to the central Baltic Sea, the coastal areas of the western Baltic Sea, like the Kiel bay, are much shallower and display differing oceanographic conditions, mainly due to the salinity distribution. The oceanography of the western Baltic Sea gives rise to specific sound propagation conditions. Experiments on the transmission loss, as well as on spatial and temporal variability in the shallow water area of the Kiel bay are presented. In order to examine the sound field properties within the water column, distributed receiver buoys and a vertical hydrophone array were utilized. A stationary, as well as a towed sound source were employed as sound projectors. The sound propagation experiments were conducted with RV ELISABETH MANN BORGESE (Institute for Baltic Sea Research, IOW).

Paper ID: 55

Profile Analysis: A framework for the study of auditory sound spectrum analysis

Jan Żera (Warsaw University of Technology)*

Corresponding author: **Jan Żera**, jan.zera@pw.edu.pl

Profile Analysis (PA) is a research approach in measuring the listeners' ability to discern the changes in the spectral envelope shape of complex tones. PA is based on a specific experimental design in which the listener is forced to perform across-frequency spectral comparisons. This is achieved by using a procedure of signal level roving to prevent the subjects from responding on the basis of their ability of detecting the change of level in a single frequency channel. The studies, initiated by D. M. Green and his co-workers in 1980s, explored the topic of PA in a thorough, systematic way. The experiments concerned the detection of amplitude increment (or decrement) of a single component in a multicomponent logarithmic complex, detection of multicomponent spectral changes, tilted spectra, or using a pedestal. The use of logarithmically spaced components accounted for the auditory filter bandwidths (ERBs) as in such spectra the same number of components fall in each and every auditory filter along a wide frequency range. Later experiments included harmonic spectra more typical of music. A novel approach in PA was to separate across-frequency spectral envelope shape comparisons in a complex tone and across-time level comparisons in given particular frequency channel. This procedure has brought new insight into timbre perception explorations in real-life conditions of sound perception, such as differentiating timbre changes in musical sounds during which both across frequency and along time comparisons are made. PA offered a new approach to the study of auditory sound spectrum analysis but was followed by only few researchers. The paper recalls results of the PA studies and provides discussion of some links between the PA and the results of listening tests conducted during a course aimed at the development of timbre evaluation skills among the students at the Chopin University of Music in Warsaw.

Paper ID: 58

Evaluation of hydroacoustic channel stationarity for reciprocal movement of transmitter and receiver

Andrzej Żak (Polish Naval Academy)*; Ryszard Studański (Uniwersytet Morski w Gdyni); Agnieszka Czapiewska (Gdansk University of Technology); Łukasz Wojewódka (Uniwersytet Morski w Gdyni); Andrzej Łuksza (Gdynia Maritime University)

Corresponding author: **Andrzej Żak**, a.zak@amw.gdynia.pl

For shallow water areas, the hydroacoustic channel is characterized by strong multipath and at the same time long memory times. In the case of reciprocal movement of the transmitter relative to the receiver, coherence times should be expected to be extremely short. Classical methods of assessing the stationarity of a channel, for example, proposed on the recommendations of ITU-R P.1407-7, in the case of hydroacoustic channels do not allow the determination of coherence times primarily due to the long memory time of the channel. In view of this, the paper proposes a method for assessing channel stationarity based on simultaneously transmitted chirp signals of increasing and decreasing frequency. The study was carried out in a laboratory pool for different rates of movement of the transmitter relative to the receiver. In the pool there was strong multipath i.e. very difficult propagation conditions for data transmission. The paper evaluates the stationarity of the channel as a function of the speed of movement of the transmitter, the bandwidth occupied by the measurement signal and its duration. The study shows that the hydroacoustic channel is not always stationary for the duration of the symbol and this assumption is often made in simulation studies of data transmission in the hydroacoustic channel.

Paper ID: 59

Sound insulation performance of cube-shaped enclosures

Krzysztof Kosała (AGH University of Science and Technology)*

Corresponding author: **Krzysztof Kosała**, kosala@agh.edu.pl

The subject of the research described in the article are the sound insulating properties of a cube-shaped enclosures, the walls of which are made of plates of homogeneous materials and double-layer baffles. As an enclosure for an omnidirectional sound source imitating a noisy machine or device, a prototype test stand for testing the acoustic properties of materials and enclosures was used. The three tested variants were enclosures with walls made of plastic plates, such as polyethylene, solid polycarbonate, and plates in the form of rigid polyethylene foam. The fourth variant was an enclosure with walls made of sandwich baffles in the form of a steel plate with a rubber layer glued on. Calculations of the effectiveness of the enclosure were carried out using the previously developed theoretical calculation model for Insertion loss (IL). The obtained results were related to the IL obtained in the course of experimental tests. The research showed slight discrepancies between the calculations and the measurement results for almost all tested materials in the entire frequency range (100-5000 Hz), with the exception of rigid polyethylene foam, for which the discrepancies were relatively the largest in the lower frequency range, i.e. below 400 Hz.

Paper ID: 60

Magnetic Pickering emulsions characterization by ultrasound attenuation spectroscopy

Bassam M Jameel (Faculty of Physics, Adam Mickiewicz University in Poznań)*; Rafał Bielas (Faculty of Physics Adam Mickiewicz University in Poznań); Arkadiusz Józefczak (Adam Mickiewicz University in Poznań)

Corresponding author: **Bassam M Jameel**, bassam.mufeed.jameel@gmail.com

A magnetic Pickering emulsion is an emulsion stabilized by magnetic nanoparticles, that accumulate at the droplet interface. However, it is crucial to characterize the stability of Pickering droplets and determine the shell thickness from an application perspective. In this research, the ultrasound attenuation was measured experimentally, and an ultrasound scattering theory based on core-shell model was implemented to analyze the measurement data. The implemented model takes into account the contribution of the shell on the droplet's core during ultrasound wave propagation.

The first part of the results focused on the theoretical calculation of ultrasound attenuation for core-shell model. The change in the ultrasound attenuation values was observed for different core radii, shell sizes, concentrations, and ultrasound frequencies. In the second part of the results, the core-shell model was used to analyze ultrasound attenuation spectra to determine the size of Pickering droplets and shell sizes. We found that the shell thickness varied with various volume concentrations of magnetic particles in the system. Additionally, we investigated the formation of Pickering emulsion under the application of an electric field. The data showed that the thickness of the shell increased compared to samples before electric field treatment.

Acknowledgments

This work was supported by project no. 2019/35/O/ST3/00503 (PRELUDIUM BIS) of the Polish National Science Centre.

Paper ID: 61

Effect on imaging quality of ultrasound probe parameters in Doppler tomography method.

Tomasz Świetlik (Katedra Akustyki, Multimediów i Przetwarzania Sygnałów, Wydział Elektroniki, Politechnika Wrocławska)*

Corresponding author: **Tomasz Świetlik**, tomasz.swietlik@pwr.edu.pl

Doppler tomography (DT) is a method that allows the reconstruction of 2D or 3D images of the interior of the examined object. For this purpose, a two-transducer ultrasound probe is used. In this method, the Doppler phenomenon and the so-called Doppler signal are used to obtain an image. Therefore, the probe is one of the most important components of the measurement system of this method.

It should be noted that Doppler tomography differs significantly from the well-known Doppler method of measuring blood flow in blood vessels. In the DT method, stationary cross-sectional images of the object under examination are obtained. In order to produce the Doppler effect in this case, the probe can move around or along the object being imaged.

This paper will present a simulation of the effect of the frequency of the ultrasound probe on the imaging quality of a single inclusion.

Paper ID: 62

Acoustic aspects of the Goseck Circle area

Katarzyna Suder-Dębska (AGH)*

Corresponding author: **Katarzyna Suder-Dębska**, suder@agh.edu.pl

Goseck Circle is an example of monumental buildings from the Neolithic period called rondels. The object was discovered in the 1990s, then archaeologically reconstructed and opened to the public in 2005. Currently, it is considered to be the oldest known object of this type, and its creation is estimated at around 4900 BC. The object is roughly circular in shape. It has one ditch and two palisade rings. There are three entrances leading to the interior of these structure, two of which are located on the south side and coincide with the places of sunrise and sunset during the winter solstice. Therefore, the Goseck Circle is considered as the oldest solar observatory, as a worship or ritual place.

A number of studies on both contemporary and archaeological objects indicate that the objects display the characteristic features depending on their intended use. Therefore, it can be assumed that if the Goseck Circle structure was to be a place of worship, then in terms of acoustics it should be characterized by such values of acoustic parameters that will also prove this. This concept was the reason for carrying out a series of numerical calculations that allowed for the determining of the selected parameters characterizing the acoustic field inside the analyzed object. The article presents and discusses the results of these numerical analyses.

Paper ID: 63

The nature of the variability of the underwater noise field on the Słupsk Bank.

Zygmunt Klusek (IOPAN Sopot)*; Aliaksandr Lisimenka (Gdynia Maritime University)

Corresponding author: **Zygmunt Klusek**, klusek@iopan.gda.pl

Analysis of underwater noise long term measurements was performed in shallow waters of the Southern Baltic Sea. Measurements were conducted in the course of seasonal changes of sound propagation conditions from typical for winter to early summer (from February to beginning of July). Investigation of similarity between basic noise metrics at two points was aimed to establish proper inference about noise levels in the area. At both sites, broadband (31.5 – 16 000 Hz) noise spectra and noise level revealed their dependency on ship traffic.

The analysis of the dependence of noise level on wind speed indicated different forms of this dependence in the two frequency ranges. For frequencies above 800 Hz, the spectrum level increases with wind speed, while in the lower frequency range it decreases.

Despite of relatively shallow site of observations occurrence of seasonal trends in the level noise in both anthropogenic and natural sources was established, what confirm and extend earlier reports regarding seasonal changes of the wind driven noise in the Baltic Sea Deeps.

Thought-provoking short-term periodicities in the noise level independent of meteorological conditions, but hypothetically dependent on vertical diel fish migrations, has been identified in some frequency bands.

Paper ID: 64

Tests of windshields for wind turbines noise measurements

Tadeusz Wszolek (Akademia Górniczo-Hutnicza w Krakowie); Maciej Kłaczyński (AGH)*; Paweł Pawlik (AGH); Bartłomiej Stępień (AGH University of Science and Technology); Paweł Małecki (AGH University of Science and Technology); Dominik Mleczko (AGH)

Corresponding author: **Maciej Kłaczyński**, maciej.klaczynski@agh.edu.pl

Measuring noise from wind turbines is a problematic metrological task due to the significant interference caused by the wind, especially in the low-frequency range. In the audible band, especially A-weighted, the impact of interference from wind is significantly less than in the low-frequency and infrasound bands. For this reason, methods are still being sought to reduce interference from wind in the lowest frequency bands effectively. Experimental tests within the scope of the work were carried out using several windshields: with a single standard spherical windscreen (90 mm diameter) at 1.5 m and 4 m height above ground level; with an additional microphone's shield (tent); with a set of the double-shell type consisting of a standard spherical windscreen made of polyurethane foam and a second shield covered with a double thin fabric (included 90% nylon with 10% admixture of polyurethane / cotton, which is often used in pop-filters) with high flexibility and a 300 mm diameter placed at the height of 1.5 m above ground level; on the board with a double windscreen at a ground level according to IEC 61400-11. An effectiveness analysis of the proposed measurement methods was carried out on the wind farm in various wind condition. Performed research indicates that the best of the tested variants, when measuring wind turbine noise especially in the low-frequency range, is to place the microphone on the board with a double windscreen according to IEC 61400-11. It is also acceptable to use a double spherical cover.

Paper ID: 65

Influence of the laboratory measurement method of the reduction of transmitted impact noise by covering floors on a heavyweight standard floor on the result

Leszek Dulak (Politechnika Śląska)*; Rafał Żuchowski (Politechnika Śląska)

Corresponding author: **Leszek Dulak**, leszek.dulak@polsl.pl

The article presents the results of laboratory measurements of the reduction of transmitted impact noise ΔL by floor coverings on a heavyweight standard floor. The tests were carried out for a floating floor with EPS T insulation in two thicknesses: 43/40 mm and 22/20 mm. Each test was carried out for two types of screed: cement and anhydrite. The tests were repeated for an additional screed load simulating furniture load and without load. An attempt was made to determine the impact of the lack of load on the test result and to check whether a small difference in the weight of the screed significantly affects the result.

Paper ID: 66

Wind turbine noise annoyance prediction in the low-frequency range

Bartłomiej Stępień (AGH University of Science and Technology)*; Tadeusz Wszółek (Akademia Górniczo-Hutnicza w Krakowie); Dominik Mleczko (AGH University of Science and Technology); Paweł Małecki (AGH University of Science and Technology); Paweł Pawlik (AGH Akademia Górniczo-Hutnicza im. Stanisława Staszica w Krakowie); Maciej Kłaczyński (AGH); Marcjanna Czapla (AGH University of Science and Technology)

Corresponding author: **Bartłomiej Stępień**, Bartlomiej.Stepien@agh.edu.pl

Currently, wind turbine noise is modelled using commonly used calculation methods such as ISO 9613-2, CNOSSOS-EU, and NORD 2000. The ISO 9613-2 and CNOSSOS-EU methods allow calculations in octave bands from 63 Hz to 8 kHz, while NORD 2000 allows calculations in one-third octave bands from 25 Hz to 10 kHz. Neither of these computational models takes into account the additional physical phenomena occurring in the low-frequency range (tonality, frequency modulation) that increase the annoyance of the noise generated by these devices. This paper presents the results of calculations using the aforementioned computational methods for modelling low-frequency noise generated by wind turbines, taking into account tonality and signal modulation determined experimentally. The suitability of the presented approach was verified by comparing the obtained calculation results with measurements taken around the wind farm.

This research has been founded by the National Centre for Research and Development - project No. NOR/POLNOR/Hetman/0073/2019.

Paper ID: 67

The Simulation of the Influence of the Doppler Effect on Wideband Hydroacoustic Signals

Zuzanna Cymerman (Politechnika Gdańska)*; Iwona Kochańska (Politechnika Gdańska)

Corresponding author: **Zuzanna Cymerman**, zuzannacymerman1@gmail.com

In Underwater Acoustic Communications (UAC) the Doppler effect, that results from the mutual motion of the system's transmitter and receiver, as well as the signal's reflection from the waves forming on the water surface, causes significant distortions of the signal reaching the receiver and reduces the achievable Bit Error Rate (BER) of the data transmission.

The article presents the design and implementation of the simulator of the Doppler effect influence on wideband hydroacoustic signals. The simulator implements two methods of modeling the influence of the Doppler effect. First of which consists of shifting the spectral components of the signal, the second - the compression or expansion of the signal in the time domain. Differences in simulation results obtained with both methods for wideband signals used in UAC systems are presented.

Paper ID: 68

Investigation of flow features and acoustic radiation of a set of rectangular cavities in a channel

Paweł Łojek (AGH University of Science and Technology)*; Katarzyna Suder-Dębska (AGH)

Corresponding author: **Paweł Łojek**, lojek@agh.edu.pl

Due to the widespread use of ventilation and air-conditioning systems in modern buildings, the issue of the generation and propagation of noise generated during the operation of these systems is becoming very important. The source of undesirable sounds have various origins -- both directly related to the devices used and related to the flow of the air through the devices, ducts and other elements that are part of these systems.

This article focuses on noise of aerodynamic origin. The paper presents the results of numerical simulations of the air flow in a channel with a set of rectangular cavities. Then, the aeroacoustic wave equation was used to determine the acoustic pressure generated by the flow. Various configurations of the cavities made it possible to study the influence of their reciprocal location on the generated sound.

Paper ID: **69**

Digital data transmission techniques in shallow-water acoustic communications

Iwona Kochanska (Politechnika Gdanska)*

Corresponding author: **Iwona Kochanska**, iwona.kochanska@pg.edu.pl

Invited paper

Paper ID: 71

Infinitesimal volume area of physical space-time in acoustics and electromagnetics

Henryk Lasota (Gdansk University of Technology)*

Corresponding author: **Henryk Lasota**, henlasot@pg.edu.pl

In practical communication engineering, the mathematics of waves, both acoustic and electromagnetic, deals usually with vast areas of physical space. The author experience in time-domain analysis of two-aspect fields in amorphous media - fluids and dielectrics has shown a far-reaching affinity of transients in acoustics, on the one hand, and wideband signals in UWB wireless communications, on the other hand.

It is worth noting that the wave relationships and equations themselves are derived by means of formal transformations relating to local interactions taking place "here and now" - in an infinitely small volume, in an infinitely small period of time. In this infinitesimal "space-time" there is an immediate interaction between phenomena. At the same time, the mechanism of this interaction can be very different depending on the physical scale of the space and time involved.

Analysis of phenomena performed in infinitesimal areas of fluids and dielectrics leads to significant results of general importance: A - it indicates the existence in both cases of a space-time with two-aspect physical dynamic properties, B - it gives a practical, engineering insight into the philosophical-practical problem of the "reality" of time/space, C - it gives a tool for determining time (frequency) ranges and linear sizes for the main classes of medium models and phenomena occurring in it - classic (continuous), statistic (granular), and quantum mechanic.

The current physics of the universe struggles with the imbalance of matter and energy. The mass-energy gap problem still needs to be addressed. A return to Lorentz's concept of ether seems potentially useful, perhaps modified by adding a trace energy-mechanical mass content to the space otherwise "endowed with only electric and magnetic properties" (original Lorentz's definition of ether accepted in 1922 by Einstein).

Paper ID: 72

Comparison of the transitional states of singing voice registers depending on the presence of the singer's formant.

Mateusz Gawlik (AGH University of Science and Technology)*

Corresponding author: **Mateusz Gawlik**, mateogawel@gmail.com

This paper provides an in-depth comparison of the transitional states of singing voice registers, specifically focusing on the influence of the singer's formant. The singer's formant, a spectral characteristic usually found in professionally trained singers, is considered crucial in the projection and resonance of the singing voice. This study examines how the presence or absence of this formant affects the transitions between vocal registers, a critical aspect of vocal performance. By presenting a comprehensive analysis, the paper seeks to broaden understanding of vocal mechanics, potentially informing better training and performance strategies for singers.

Paper ID: 73

Low-Power Underwater Modem for Shallow Water Communications

Jan H. Schmidt (Politechnika Gdańska Wydział Elektroniki, Telekomunikacji i Informatyki Katedra Systemów Sonarowych); Iwona Kochanska (Politechnika Gdańska)*; Aleksander M. Schmidt (Politechnika Gdańska Wydział Elektroniki, Telekomunikacji i Informatyki Katedra Systemów Sonarowych)

Corresponding author: **Iwona Kochanska**, iwona.kochanska@pg.edu.pl

The low-power underwater acoustic modem is usually an important component of the Underwater Wireless Sensor Network (UWSN). Network nodes have predetermined energy resources that will not be replenished during the life of the node. In shallow waters, multipath propagation is constantly occurring and for the modem to work effectively, solutions to overcome them must be used, which will also meet the important criterion of energy efficiency. The article presents the concept of a low-power underwater modem using BFSK modulation and the fast frequency-hopping spread spectrum (FFHSS) technique. The results of simulation and experimental tests, which were carried out to determine the performance of the modem, are included. Simulation tests were performed using a Watermark simulator, and experimental tests in a model pool.

Paper ID: 74

A Design of an Acoustic Coupler for Calibration of Pressure Sensors at Ultra Low Frequencies

Karol Jakub Listewnik (Gdynia Maritime University / Uniwersytet Morski w Gdyni)*

Corresponding author: **Karol Jakub Listewnik**, k.listewnik@we.umg.edu.pl

The article aims to present a coupler developed for the calibration of alternating pressure of the pressure sensors at ultra-low frequencies up to 0.1 Hz for the Central Office of Measures (GUM). This study is part of the project "Concept for the construction of metrological infrastructure in the area of underwater acoustics at GUM", which is part of the Polish Metrology program. The growing demand for research of marine objects in the field of infrasonic underwater noise and research of the hydrodynamic field of ships requires ensuring the reliability and repeatability of recorded data and it starts with reliable calibration of pressure sensors. The choice of calibration method was based on a detailed and extensive analysis of calibration methods and similar solutions. The proposed solution is based on an eccentric mechanism driven by a stepper motor. The article contains an analysis of the literature of similar solutions and presents the theoretical basis, describes the designed coupler structure, configuration of the measurement system and a summary.

Paper ID: 75

Validation of Adaptive Categorical Listening Effort Scaling (ACALES) for Polish language.

**Anna Pastusiak (Adam Mickiewicz University)*; Jędrzej Kociński (Adam Mickiewicz University);
Anna Warzybok-Oetjen (Universität Oldenburg)**

Corresponding author: **Anna Pastusiak**, anna.pastusiak@amu.edu.pl

Introduction: Considering the complexity of perceiving and properly processing speech signals, it is important in audiological diagnostics to assess not only intelligibility itself but also the so-called auditory effort, understood as a mental load needed to understand acoustic information in speech signals.

Purpose: The aim of the study was to prepare and validate in terms of the accuracy and repeatability of results (test-retest) the Polish version of the Adaptive Categorical Listening Effort Scaling (ACALES) test. The speech material used was the Polish Matrix Sentence Test. 60 listeners participated in the measurements - 20 younger and 20 older individuals with normal hearing, as well as 20 individuals with sensorineural or mixed hearing loss of varying degrees. Using the Oldenburg Measurement Application (OMA) software listening effort was assessed using a 13-point scale in various acoustic conditions including stationary, modulated, and cafeteria noises. In addition, speech recognition thresholds (SRT) and slope were determined adaptively under the same masking conditions.

Results: Similar to speech intelligibility, the influence of the masker type on the measured listening effort was observed - it was usually greater in the case of stationary noise compared to modulated signals. Listening effort decreased as the signal-to-noise ratio (SNR) value increased. At unfavourable SNR values, listening effort ratings depended on measured intelligibility to a greater extent than at higher SNR values. Older, normal-hearing listeners and people with hearing loss rated their listening effort higher compared to young, normal-hearing listeners.

Conclusion: It has been shown that the Polish version of the ACALES is a reliable, repeatable, and simple tool characterized by a small variability between test/re-test values and can provide complementary information to the value of speech intelligibility, supporting the multi-faceted assessment of the patient's ability to effectively hear in the context of communication situations.

Paper ID: 77

Measurement verification of model calculations results of noise distribution around large industrial plants

Tadeusz Wszolek (Akademia Górniczo-Hutnicza w Krakowie)*

Corresponding author: **Tadeusz Wszolek**, twszolek@agh.edu.pl

Noise mapping of large industrial plants is typically carried out in preparing Integrated Pollution Prevention and Control (IPPC), environmental impact assessments and as part of strategic noise mapping. The construction of an acoustic model of a large plant at the development stage is similar to the modelling of other facilities. Essential differences arise at the calibration and verification stage of such a model. In an industrial plant, noise sources are distributed over a large area and noise emissions are usually measured at the plant boundary, at varying distances from the noise sources. Noise sources in large cities are distributed over an even larger area, but the calculations can be verified directly in their surroundings (e.g. next to a road), with the influence from other sources eliminated. In addition, the layout of the sources is repeatable (roads, railways, etc.). These are features that increase the accuracy of the modelling. In the case of an industrial plant, which is often seen as a black box, the points for calibrating the model are outside. Then the calibrated (measured) level is not the emission from an individual source but the summed emission level from all sources on the site. The noise emission from noise sources at the measurement point strongly depends on the attenuation along the propagation path. The magnitude of this attenuation for each source is different, as it depends on the location of the source relative to the measurement point and the obstacles between the source and the measurement point. As the EU recommended computational models (ISO 9613-2 and CNOSSOS) allow calculations to be performed under specific weather conditions, the problem of measurement verification of the model becomes even more important.

The paper focuses on the consistency of weather conditions and measurement verification and their influence on the result of noise prediction in the surroundings of a large industrial plant. The results of control point calculations using ISO 9613-2, CNOSSOS algorithms and the Nord 2000 model, which allows calculations under practically any weather conditions, are shown. The results of the analyses were compared with the measured results at the control points under 'real' weather conditions.

Paper ID: 78

Identification of errors in the digital transmission paths of radio stations

Marcin Pater (Uniwersytet Rzeszowski)*; Marcin A Grochowina (Uniwersytet Rzeszowski)

Corresponding author: **Marcin Pater**, *marcin.pater000@gmail.com*

Radio stations currently use a hybrid method of broadcasting. The transmission between the studio and the transmitter is digital. In the transmitter, the digital signal is converted to analog form and transmitted using AM or FM modulation.

The identified problem are transmission errors in the digital path. Single cases of transmission errors are not uncommon and happen in most systems. However, repeated errors occurring in clusters are usually a sign of damage to the transmission path and require intervention.

The article presents an exemplary solution that allows automatic detection of some errors that manifest themselves in the identified way. In order to identify transmission errors, basic statistical methods were used that allowed the creation of a reference data set on the basis of which it is possible to identify the fact of an error based on patterns and algorithms from the machine learning area.

People associated with the radio industry are keenly interested in studying this phenomenon because there are currently no reliable solutions that would allow automatic detection and identification of such problems.

Paper ID: 79

Wpływ wykorzystania układu rezonatorów w strukturze kryształu sonicznego na jego skuteczność

Julia Wesołowska (Silencions sp. z o.o.)*

Corresponding author: **Julia Wesołowska**, julia.wesolowska@silencions.com

Niniejszy referat dotyczy tematu warstwowych struktur kryształów sonicznych. Kryształy soniczne są to periodyczne układy rozpraszaczy akustycznych umieszczone w jednorodnym ośrodku. Osiągają one skuteczność poprzez różnicę impedancji występującą pomiędzy ośrodkiem, a rozpraszaczem. Struktury te cechuje możliwość dostrojenia układu do wybranego pasma częstotliwości, a także możliwość swobodnego przepływu powietrza. W referacie omówiony zostanie wpływ zastąpienia rozpraszaczy w strukturze kryształu sonicznego układem rezonatorów (poprzez wykonanie otworów w cylindrach) na ich skuteczność w wybranym paśmie częstotliwości. Spadek transmisji został obliczony analitycznie, a następnie zweryfikowany przez pomiary wykonane w warunkach pola swobodnego. Analiza skuteczności rozwiązania została potwierdzona przez pomiary z wykorzystaniem głośnika kierunkowego jako źródła dźwięku oraz dwóch konfiguracji kryształów sonicznych. Pierwszego, zbudowanego z rozpraszaczy oraz drugiego zbudowanego z rezonatorów Helmholtza, uzyskanych poprzez wykonanie otworów w cylindrach budujących kryształ.

Paper ID: 80

Practical aspects of diffuse reflection and sound diffraction modeling in room acoustics simulations

Piotr Pękala (AkustiX, Adam Mickiewicz University)*

Corresponding author: **Piotr Pękala**, p.pekala@akustix.pl

Most modern programs for modeling room acoustics contain implementations of algorithms that enable modeling of diffuse reflection and diffraction of sound inside rooms. However, these algorithms are often based on different mathematical models, require different sets of input data, and also differ significantly in computational complexity and precision of the calculation results. The use of these capabilities of simulation programs is possible provided access to data on the characteristics of the sound scattering coefficients of the materials used. The most commonly used coefficients are these obtained in a diffuse field.

The presented paper discusses the implementation of diffuse reflection and sound diffraction modeling algorithms in the most popular simulation programs.

In addition, the influence of modeling these phenomena on the accuracy of the obtained results was analyzed on exemplary room models.

Paper ID: 81

The use of psychoacoustic tests and objective methods of hearing examination in the study of Alzheimer's disease patients

Jędrzej Kociński (Department of Acoustics, Faculty of Physics, Adam Mickiewicz University, Poznań)*; Andrzej Wiecher (Department of Acoustics, Faculty of Physics, Adam Mickiewicz University, Poznań); Anna Pastusiak (Adam Mickiewicz University); Magdalena Puchalska (Department of Acoustics, Faculty of Physics, Adam Mickiewicz University, Poznań); Natalia Sudaj (Department of Acoustics, Faculty of Physics, Adam Mickiewicz University, Poznań); Marcin Górniak (Specialist Medical Practice, psychiatrist)

Corresponding author: **Jędrzej Kociński**, jedrzej.kocinski@amu.edu.pl

Background: The prodromal phase of Alzheimer's disease (AD) is characterized by the emergence of mild cognitive impairment that falls short of the diagnostic criteria for dementia. During this phase, individuals commonly exhibit subtle memory deficits, word-finding difficulties, challenges in problem-solving, and overall cognitive decline, which often progress to the development of full-blown Alzheimer's dementia. Early identification and intervention during the prodromal phase are crucial for implementing appropriate treatment and support strategies that may potentially slow down disease progression.

Materials and methods: This study employed a comprehensive set of psychoacoustic and objective methods of hearing examination, ie.: temporal gap detection, amplitude modulation detection, interaural time/level difference discrimination thresholds, speech reception threshold in noise, distortion product otoacoustic emissions (DPOAEs), auditory brainstem responses (ABRs), and auditory evoked potentials (P300). A small group of patients in different stages of AD were tested and compared to individuals with normal hearing.

Results: Considering the fact that only a small group of patients have been tested so far, case study analyzes were performed. Overall, when compared to the reference values, the majority of individuals with AD showed elevated speech reception thresholds. Moreover, there were notable elevations observed in temporal gap detection thresholds and binaural parameters, concomitant with a significant prolongation of the P300 wave latency, as indicated by objective measurements.

Conclusions: Although the data collected in this study did not yield conclusive statistical findings regarding changes in the measured psychoacoustical parameters in AD patients, the results are promising. Further research, incorporating speech, visual, and memory tests, will be conducted to deepen our understanding of the auditory perception changes associated with AD.

Paper ID: **83**

Modeling Human Sound-Source Localization: Current State and Future Directions

Piotr Majdak (Austrian Academy of Sciences)*

Corresponding author: **Piotr Majdak**, piotr.majdak@oeaw.ac.at

Spatial hearing allows us to orient ourselves and navigate in a 3D environment. The acoustic basis for 3D spatial hearing is described by the listener-specific head-related transfer functions (HRTFs). While much attention has been put on the aspects along the left/right dimension, spatial hearing goes beyond the lateral dimension, and such investigations often require novel modeling approaches. In this talk, we will focus on the dimensions of sound localization that are particularly sensitive to listener-specific HRTFs, that are, near distances (sound externalization/internalization) and sagittal planes (top/down, front/back). We will discuss recent psychoacoustic findings and computational models aiming at simulating mechanisms underlying the process of sound localization. Further, we will explore the possibility of employing Bayesian inference as a quantitative method to predict 3D human sound localization in dynamic auditory scenes and including self-motion. As outlook, we will describe a unified probabilistic framework potentially able to integrate outcomes from various perceptual experiments to develop functional models of space perception, discussing its advantages and its limits and future directions.

Paper ID: 86

Beamforming in nearfield - metaheuristic approach and speech intelligibility tests

Agnieszka Wielgus (Wrocław University of Science and Technology)*; Bogusław Szlachetko (Wrocław University of Science and Technology); Michał Łuczyński (Wrocław University of Science and Technology)

Corresponding author: **Agnieszka Wielgus**, agnieszka.wielgus@pwr.edu.pl

A set of microphones spatially arranged in space in a specific pattern is called a microphone array. Such an array has many applications, inter alia: sonars, radars, or speech processing. It can be used to extract and enhance the signal of interest from its observation corrupted by other interfering signals, such as noise or to estimate the direction of arrival of a source. Since the microphones are in different places in space, the phase of the signal components that arrive to each of the microphone can be different and some frequencies can be attenuated. Therefore, the array can be perceived as a spatial filter that consolidates the acoustic signals received by individual microphones to form a beam. Such process is called beamforming.

In this paper we focus on a problem in which the desired signal (speech signal) is interfered by other signal with partially overlapping band but with different localization. Our goal is to attenuate the interfering signal. We experimentally study the method in which microphones do not have to be equally spaced and all information regarding signal phase is hidden in a transfer function of the microphone. We focus on determining the microphones positions to minimize and FIR filter coefficients so that the actual output the beamformer is as close as possible to the desired one in the sense of ℓ_2 norm. To solve this problem, we use a metaheuristic algorithm. Since the interfering signals, i.e. background noise reduce speech intelligibility (SI), we study how the proposed microphone matrix influences this parameter (SI) - a variable, being an index of the comprehensibility of speech signals. SI is defined as the average percentage of words or phonetic units that human listeners can recognize.

Paper ID: **87**

Investigating the Restorative Properties of Natural Soundscapes

Dorota Młynarczyk (AGH University of Science and Technology)*

Corresponding author: **Dorota Młynarczyk**, dorotam@agh.edu.pl

With the increasing levels of stress and the challenges associated with psychological restoration, natural soundscapes have gained attention for their therapeutic qualities. However, there is a need for an objective classification system to facilitate psychoacoustical research in this area. This paper focuses on analyzing the restorative properties of diverse natural soundscapes. By examining acoustic, acoacoustic, and psychoacoustic parameters, as well as conducting psychoacoustic tests utilizing virtual reality tools, this study aims to provide a comprehensive understanding of the factors that contribute to the restorative effects of these soundscapes. The research results and their analysis have led to the creation of a classification of soundscape parameters that significantly affect the ratings of their restorative properties. In the future, further analyses will allow for the development of a guide that describes which soundscape parameters and their values are crucial for their positive restorative evaluation.

Paper ID: 88

Comparative analysis of selected voice parameters of patients with obstructive pulmonary disease and dysphonia.

Karolina Węglarz (Krakowska Akademia)*; WSZOŁEK WIESŁAW (AGH); Elżbieta Szczygieł (Akademia Wychowania Fizycznego w Krakowie); Daria Hemmerling (AGH)

Corresponding author: **Karolina Węglarz**, karolinaw.roz@gmail.com

A quality of voice is an important matter in communication, and can determine self-esteem and relationship quality. Speech pathologies can be a serious disability of the accusation, leading in extreme cases to social exclusion. Voice problems are similar both among people working with professional voice and patients with respiratory disease, including chronic obstructive pulmonary disease.

The purpose of the work was a comparative analysis of selected voice parameters of patients with obstructive pulmonary disease and dysphonia.

Research material: Research tests were taken on a group of 61 people: 30 healthy people (mean age 25.1 years), 16 patients with COPD (mean age 67.4 years) and 15 patients with dysphonia (56.4 years).

In order to obtain changes in the acoustic signal, characteristic for dysphonia and obstructive pulmonary disease, it was necessary to verify according to: body position and selected voice parameters.

Body position was assessed using the photogrammetric method. The three-plane position of the body in space was established. In order to study the acoustic signal of speech, an analysis was carried out in the time and frequency domain of the collected voice recordings. In contrast to the "classical" methods of speech signal assessment and analysis, the directions of research mentioned and conducted by many authors bring little when it comes to speech pathologies. The acoustic signal of pathological speech should be justified from the three-point source of this signal: the process of articulation - the process of origin - the stage of deformation of one and the other process by determination.

As a result of the research, the parameters of the speech acoustic signal were obtained, which provide additional information about changes in the sound source, which manifest themselves in the form of deformation of the sound signal.

The research method presented in the article will provide the patient with comprehensive and necessary diagnostics, as well as the process of treatment and rehabilitation.

Paper ID: 89

Diagnosis of acoustic hazards of the environment and its identification problems

Wojciech Michał BATKO (Academy of Applied Sciences in Krosno)*

Corresponding author: **Wojciech Michał BATKO**, batko@agh.edu.pl

The problems of control and control of the state of acoustic hazards of the environment have a certain unrecognized scientific and application potential. This is because its identification research dimension has a number of specific properties .They shape the performance peculiarities of the model process, describing the recognized mechanisms: noise generation and propagation, classification of noise hazard states and their forecasts.

Failure to comply with the methodological requirements inherent in identification tasks aimed at: the genesis classification and prognosis of the state of environmental noise hazards - in a manner consistent with their perception by humans - is currently the source of a number of paradoxes and related errors of interpretation.

The speech will review them. The correctness of the decibel algebra will be analyzed, and its corrections will be proposed, opening up new fields of research for the diagnosis of the state of acoustic hazards. The role of proper selection of metrics for decibel comparisons of measurement results, in the process of classifying the state of noise hazards, is outlined. It was found that the currently used Euclidean distance measures in such a process can raise significant objections. Related : methodological, interpretive and application implications are outlined.

The need for new measures for the analysis of comparisons and exceedances of permissible sound levels, free from the limitations of current control practice, was pointed out.

The issues analyzed in the paper were supplemented by an analysis of the problems present in the estimation of the uncertainty of research diagnoses , present in the practice of controlling the state of acoustic hazards of the environment, and the presentation of paths leading to their solution.

Paper ID: 90

Analysis of Dynamic Mechanical Properties of Composite Materials for Electric Guitar Construction

Paweł Małecki (Warsaw University of Technology / Sieć Badawcza Rafał Perz / RUF Guitars)*; Paula Pietrzak (Warsaw University of Technology); Rafał Perz (Warsaw University of Technology / Sieć Badawcza Rafał Perz / RUF Guitars); Filip Zakrzewski (Warsaw University of Technology / Sieć Badawcza Rafał Perz / RUF Guitars); Marek Matyjewski (Warsaw University of Technology)

Corresponding author: **Paweł Małecki**, pawel.malecki2.dokt@pw.edu.pl

In recent years, composites have been presented widely as an alternative to traditional materials in many technological applications. Composite materials can be used for manufacturing musical instruments. In the case of an electric guitar, the guitars body, neck and fretboard can be made out of the composite structures. The mechanical properties of composite and epoxy-based materials may determine the final timbre of the instrument. Therefore, analysis of the dynamic response of those materials should be made, to ensure the optimal structural composition. In this paper, three different composite and epoxy-based materials were examined in terms of their dynamic mechanical properties. Firstly, samples of different composite materials were prepared and measured to obtain accurate geometry and mass data. Next, the samples underwent experimental modal impact hammer testing and then obtained output data was analyzed. As preliminary state of research storage modulus was calculated to observe differences in dynamic properties of the evaluated variants of composite materials. Obtained results indicate the possibility of differentiating the variants of composite materials to obtain the best fit for manufacturing the body of an electric guitar.

Paper ID: 92

Contextual Localization Bias For A Wide Range Of Azimuth And Frequency Conditions

Bernhard Laback (Austrian Academy of Sciences)*

Corresponding author: **Bernhard Laback**, Bernhard.Laback@oeaw.ac.at

The perceived azimuth of a sound source is biased by a preceding source (precursor), typically, towards midline (medial) by a lateral and towards the side (lateral) by a central precursor. Little is known about effects of intermediate precursor azimuths and the contribution of low and high frequency regions. We tested the hypothesis that for a certain intermediate precursor azimuth, lateral and central biases cancel each other out. Ten normal-hearing listeners localized 300-ms targets following 600-ms precursors using a head-pointing task in a virtual audio-visual environment. Both target and precursor azimuths were systematically varied across the azimuth range from left (-90°) to right ($+90^\circ$). Stimuli were white noises, filtered with listener-specific head-related transfer functions. Low-pass (0.5-2 kHz), high-pass (2.8-16 kHz), and broadband (0.5-16 kHz) conditions were tested to investigate the role of frequency regions dominated by different localization cues: interaural time differences in low-pass, interaural level differences and spectral shape in high-pass, and all three cues in broadband stimuli. Precursor effects were overall strongest for target azimuths of $\pm 70^\circ$. Cancellation of lateral and central biases was found only for $\pm 70^\circ$ -targets, for a mean precursor azimuth of 58.3° . Importantly, the data showed selective spatial contrast enhancement for targets preceded by azimuthally matched Ps. Patterns of precursor effects were relatively similar across frequency regions.

Paper ID: 94

Estimation of the improvement of the impact sound insulation of a carpet floor covering on a wooden floor based on the results of tests carried out on a massive floor

Łukasz Nowotny (Instytut Techniki Budowlanej)*; Jacek Nurzyński (Instytut Techniki Budowlanej)

Corresponding author: **Łukasz Nowotny**, l.nowotny@itb.pl

This paper presents the relationship between the sound insulation properties of carpet floor coverings on the massive and lightweight reference floor structures. Most floor covering impact sound insulation tests are performed on a massive reference floor. There is actually no data on lightweight floor, which means that the possibilities of damping the impact sounds of floors on such structures are unknown. It turns out that it is achievable to estimate the parameters of impact sound insulation of carpet coverings installed on a wooden floor on the basis of tests performed on a massive reference floor. The proposed method uses the mobility parameters of the elements involved in the acoustic test. The use of this method allows to reduce the number of tests necessary to select the appropriate solution for damping the impact sound energy in the lightweight floor structures.

Paper ID: 95

Experimental setup design to evaluate acoustical privacy protection in small enclosed compartments.

Alois Sontacchi (Institute of Electronic Music and Acoustics, Graz, Austria)*; Christian Blöcher (Institute of Electronic Music and Acoustics, Graz, Austria Institute of Electronic Music and Acoustics, Graz, Austria); Thomas Hatheier (AUDIO MOBIL Elektronik GmbH)

Corresponding author: **Alois Sontacchi**, sontacchi@iem.at

Privacy protection is an upcoming topic in our society caused by increased individual mobility and forced availability by telephone. Acoustic communication in small, closed compartments exhibits a challenge to establish a private sphere for a single user without heavily affecting the acoustical surrounding, e.g. in a quiet environment, for other persons. For a specific use-case in car compartments a recently developed approach will be examined within a listening test. To ensure control over several conditions of the experimental setting while still providing the listeners a comfortable situation mimicking real conditions a specific real-time capable setup in an anechoic room is used.

Within the experiment different positions for both speaker and would-be listener are examined under multiple driving conditions. Psychoacoustic principles like spectral and spatial auditory masking of signal-dependent broadband noise as well as signal-dependent temporal distractors are evident and adjustable components of the evaluated approach. Therefore, in the proposed experimental setup the listening subjects initially have to adjust the level of the broadband component individually to the point of perfect masking of presented speech signals. However, while these levels should guarantee complete unintelligibility, they will cause the most affecting loudness increase in the car cabin potentially causing increased passenger annoyance. Therefore, these levels will provide the anchors to start an individual adaptive adjustment procedure. Subjects presented with masked spoken sentences will echo the recognized parts immediately. Their responses will be evaluated by an automatic speech recognition system in real-time to guarantee sufficient masking. Within this procedure the broadband noise levels will be readjusted by additionally applying temporal compact distractors. Thus, the overall loudness will be reduced while preventing listening in.

Paper ID: 99

A new, bio-inspired microphone design

Daniel Beer (Fraunhofer IDMT)*; Andreas Männchen (Fraunhofer IDMT); Claudia Lenk (TU Ilmenau); Martin Ziegler (TU Ilmenau); Tzvetan Ivanov (TU Ilmenau)

Corresponding author: **Daniel Beer**, daniel.beer@idmt.fraunhofer.de

Diverse trending technologies such as the voice control of machines or automatic acoustic condition monitoring are creating an ever-increasing demand for a microphone technology that is well-suited to as many different sound situations as possible. This article presents a novel bio-inspired microphone and uses measurements to estimate its potential, compared to conventional microphones, as an acoustic sensor in future applications.

Paper ID: 103

Prediction of effects of impact pile driving noise on marine fauna in the PEEZ: A comparison of different scenarios

Zygmunt Klusek (IOPAN Sopot)*; Aliaksandr Lisimenka (Gdynia Maritime University)

Corresponding author: **Zygmunt Klusek**, *klusek@iopan.gda.pl*

The construction of wind power plants in offshore areas is usually associated with the generation of high energy and high sound pressure.

In the Polish Exclusive Economic Zone (PEEZ), the construction of a complete network of wind power generator fields is planned, which will result in an increase in the level of underwater acoustic field both during the construction phase and during the operation of the generators.

The negative and sometimes destructive impact of high amplitude and high energy sounds on marine organisms is relatively well recognised, at least for some types of animals such as mammals and some fish species.

Hence, the estimation of the values and extent ranges of basic metrics of underwater sound associated with piling is undergoing constant attention from administrative bodies and is an interesting research topic.

This paper presents the results of modelling studies carried out to predict the ranges of impact of sound associated with piling on marine organisms.

Numerical modelling of acoustic wave propagation was carried out using an approximation of the wave equation in the form of the parabolic equation of acoustics.

The sound sources were located in several planned wind power plant areas, mainly located north of Słupsk Bank.

Various scenarios were considered to simulate the range of noise impacts, such as seasonal variations in sound propagation in the basin, pile diameter and/or application of different sound mitigation methods.

Paper ID: 106

Micro-perforated stretched ceilings for acoustic, lighting and climate design

Christian Nocke (Akustikbüro Oldenburg)*

Corresponding author: **Christian Nocke**, nocke@akustikbuero-oldenburg.de

Stretched foils used as ceilings, wall coverings and other set-ups have been applied for more than 30 years. By introducing a nearly invisible micro-perforation into the stretched material the foil becomes highly sound absorptive. The classical set-up of a micro-perforated sound absorber consists of a micro-perforated panel in front of an air cavity. The sound absorption coefficient of these set-ups can easily be calculated with a high accuracy according to the well-known approximation of D.-Y. Maa if all defining geometrical parameters (diameter of microperforation, distance between orifices, panel thickness and air cavity depth) are known. Measurements in the reverberation chamber are presented for several set-ups.

These materials are applied in architectural design. Here the combination of acoustic absorption, lighting design and climatization is most interesting – three functions in one ceiling set-up. Furthermore optically transparent sound absorbers are available to cover glass surfaces.

Different applications in rooms will be presented from various projects.

Paper ID: 107

New draft DEGA guideline 103-1 in sound protection classes

Christian Nocke (Akustikbüro Oldenburg)*

Corresponding author: **Christian Nocke**, nocke@akustikbuero-oldenburg.de

The DEGA recommendation 103 (DEGA-Empfehlung – Schallschutz im Wohnungsbau und Schallschutzausweis) has been introduced in the year 2009 and includes a classification scheme for dwellings. Seven classes are defined. The classification is based on different criteria for air borne noise, impact noise and other quantities. In 2018 a revised version has been published. Both version relied on classical quantities such as air born sound insulation R'_{w} and impact sound insulation $L'_{n,w}$.

A new version has recently published as a draft DEGA guideline 103-1 (Entwurf zur DEGA-Richtlinie 103-1 "Schallschutz im Wohnungsbau, Teil 1"). In this new draft the idea of seven classes has been taken over. The classification is based on traditional values such as R'_{w} and $L'_{n,w}$ but also offers the use of the weighed sound level differences $D_{nT,w}$ and weighed standardized impact sound pressure level $L'_{nT,w}$. It is suggested to use the later quantities. This dual track approach allows a better design and will lead to a higher acceptance among acousticians and other users.

The new draft is presented and will be discussed in relation to other approaches for sound protection in dwellings.

Paper ID: **109**

Annoyance of noise penetrating partitions in multi-family and multi-function buildings.

Hanna Turkowska (Instytut Techniki Budowlanej)*

Corresponding author: **Hanna Turkowska**, *h.turkowska@itb.pl*

Multi-family residential buildings often combine residential and commercial functions. At the same time, the amount of time spent in the home is increasing, partly due to the increasing prevalence of remote working. In such a situation, the problem of providing suitable acoustic conditions for work and rest becomes particularly important. Many works indicate that standard - single - number methods for assessing the acoustics of partitions are insufficient to determine whether occupants are adequately protected from noise. The main purpose of this study is to assess the annoyance of noise penetrating different types of partitions. The spectral waveforms of exemplary noises penetrating into living spaces were analysed, and the results obtained were related to indices for assessing noise annoyance. This indicates the need for further work on methods for assessing the building envelope in residential and commercial buildings.

Paper ID: **111**

Acoustic screen as a practical anti-noise protection

Janusz Piechowicz (AGH University of Science and Technology)*

Corresponding author: **Janusz Piechowicz**, *piechowi@agh.edu.pl*

Acoustic screens are commonly used in Poland and in many countries as the only protection of noise-prone areas. They are used both in the outdoor environment and in the working environment in industrial rooms and offices. The history of the use of acoustic screens dates back to the second half of the 20th century. Since then, they have been used to reduce noise from roads, railways, airports, manufacturing plants, and municipal noise, as well as for many other noise sources. The effectiveness of an acoustic screen is a function of many factors that must be considered in the design process. The article presents the multi-variant application of acoustic screens, discusses the methods of testing acoustic parameters of screens in laboratory and in situ conditions.

Paper ID: **112**

Selected problems of active plate vibration suppression

Lucyna Leniowska (University of Rzeszow)*

Corresponding author: **Lucyna Leniowska**, *l.leniowska@ur.edu.pl*

The main aim of the control systems designed for planar flexible structures is to cancel their vibrations and related acoustic radiation as much as possible. This problem is often solved by the application of active methods. This paper presents the derivation of the models for planar structures with surface mounted piezoelectric actuators. The first approach consists in modelling the structural dynamics in the form of the partial differential equations (PDE) derived from physical principles such as the balance of forces and moments. In the second approach, a parametric system identification procedure is employed to establish a mathematical model of the considered system on a basis of the data collected from the measurements. The main objective is to estimate the control-oriented models that are suitable for designing controllers. On the basis of the models derived, the adaptive control algorithms based on solution of Diophantine equation are used to suppress circular plate vibrations. The results of performed simulations and tests are included and discussed.

Paper ID: 113

Reducing the impact of fundamental frequency on the HFCC parameters of the speech signal

Stanislaw Gmyrek (Wroclaw University of Science and Technology)*; Robert Hossa (Wroclaw University of Science and Technology); Ryszard Makowski (Wroclaw University of Science and Technology)

Corresponding author: **Stanislaw Gmyrek**, stanislaw.gmyrek@pwr.edu.pl

The voiced parts of the speech signal are shaped by glottal pulse excitation, the vocal tract, and the speaker's lips. Semantic information contained in speech is shaped mainly by the vocal tract. Unfortunately, the quasiperiodicity of the glottal excitation, in the case of HFCC parameterization, is one of the factors affecting the significant scatter of the feature vector values by introducing ripples into the amplitude spectrum. This paper proposes a method to reduce the effect of the quasiperiodicity of the excitation on the feature vector. For this purpose, blind deconvolution was used to determine the vocal tract transfer function estimator and the corrective function of the amplitude spectrum. Then, based on the obtained HFCC parameters, statistical models of individual Polish speech phonemes were developed in the form of mixtures of Gaussian distributions, and the influence of the correction on the quality of classification of speech frames containing Polish vowels was investigated.

Paper ID: 114

Algorithm for detection of wave packets in a circular waveguide

Piotr Wrzeciono (Warsaw University of Life Sciences, Institute of Information Technology)*; Michał Szymański (Warsaw University of Life Sciences, Institute of Information Technology); Hydayatullah Bayat (Warsaw University of Life Sciences, Institute of Civil Engineering)

Corresponding author: **Piotr Wrzeciono**, piotr_wrzeciono@sggw.edu.pl

This paper presents an algorithm for detecting wave packets in a circular waveguide. The waveguide terminated with a concrete plug was used to test the method. The concrete was made in accordance with the Eurocode standard. During the tests, a significant difference was observed between the behavior of the speaker and the concrete plug. The pulse reflected from the plug maintained its shape regardless of the sound level. The reflection of the pulse from the speaker's diaphragm resulted in a significant change in the form and duration of the wave packet. These changes were dependent on the sound level of the wave packet. As a result of these modifications was a significant difference between the measurement uncertainty of detecting a pulse reflected from the concrete and the speaker. In the case of reflection from the concrete plug, an uncertainty of 0.036% was obtained. The smallest measurement error value for the pulse reflected from the speaker was 2.5%.

Paper ID: 115

Selected acoustic structures for effective sound absorption at low frequencies

Patrycja Świrk (Uniwersytet Rzeszowski)*; Lucyna Leniowska (University of Rzeszow)

Corresponding author: **Patrycja Świrk**, pswirk@ur.edu.pl

The article presents a summary of the results of absorption tests for selected sound-absorbing-insulating materials: commonly used acoustical systems and composite materials of specially composed composition. In addition, we propose a new type of metamaterial in the form of a multi-layered acoustic system, which consists of an insulating material and a core in the form of a profiled steel plate loaded with a point mass, vibrating in an air gap environment. The research aims to evaluate the sound absorption performance of selected materials in the low frequency range. The results confirmed the very good absorption properties of the developed composite materials. In addition, promising absorption coefficient values were also obtained for the acoustic metamaterial in the case of matching the point mass to the local resonance.

Paper ID: 116

Validation of the measurement data for different heights of a microphone position in outdoor environment

Andrzej C. Staniek (Główny Instytut Górnictwa)*

Corresponding author: **Andrzej C. Staniek**, astaniek@gig.eu

One of the major problems when performing measurements of noise generated in outdoor environment is assessment of the influence of the microphone position (height). For measurement of noise generated by wind turbines it is important as in EN 61400 standard the measurement technique specifies mounting of the microphone on a mounting board on the ground level. So for the other microphone positions, practically demanded especially for long term monitoring, it should be carefully analysed and transfer function should be evaluated. Other problem which is under investigations is the influence of wind and the correction due to wind speed ought to be estimated.

Paper ID: 117

Cloning the voice and speech of Piotr Fronczewski for Polish speech synthesis.

Krzysztof Szklanny (Polsko-Japońska Akademia Technik Komputerowych)*

Corresponding author: **Krzysztof Szklanny**, kszklanny@pjwstk.edu.pl

The quality of synthetically generated speech has improved significantly in recent years, largely due to the technological development of speech synthesis systems, in particular those based on deep neural networks (DNN). However, the problem of emotion in speech synthesis still remains a challenge. Most of the existing speech synthesis systems do not convey the pervasive emotional contexts in human-human interaction. The lack of expression limits the emotional intelligence of current speech synthesis systems. This work aimed to develop a recording method for preparing a balanced corpus of emotional recordings in the Polish language for use in speech synthesis based on artificial intelligence (AI) algorithms. An essential aspect of the work was the selection of a voice-over artist who would allow the recording of the spectrum of an actor's voice, emphasizing the actor's interpretations and emotions derived from the content. Outstanding actor Piotr Fronczewski was chosen for the role.

Paper ID: 126

Design and practical realization of an amplifier constructed on the basis of Nuvistors used in the preamplifier circuit

Tomasz Kopciński (Politechnika Wrocławska)*; Maurycy J. Kin (Wrocław University of Science and Technology)

Corresponding author: **Tomasz Kopciński**, 253179@student.pwr.edu.pl

The poster aims to show the method of designing, practical realization and measurement of an electroacoustic amplifier constructed on the basis of electron tubes, especially Nuvistors used in the preamplifier circuit. Nuvistor tubes 6N52S were used in the input stage and phase inverter system in the self-symmetry system. The single channel of power amplifier uses a pair of EL84 power pentodes working in a Push-Pull system. The amplifier also uses a passive tone control system in the Baxhandall system.

The paper presents the complete stages of designing, construction and measurements. The realized device and the measurements as well as the subjective tests confirmed the possibility of using Nuvistor lamps in devices working with an acoustic signal. The use of Nuvistors allowed to reduce the anode voltages compared to the traditionally used ECC83 triodes. Also, the reduction of the dimensions of the device and achieving a frequency bandwidth of -2.6dB/+0.0dB from 20Hz to 20kHz, are available.

Paper ID: 132

The effect of ultrasonic noise on a worker's ability to perform their basic tasks

Jan Radosz (Central Institute for Labour Protection - National Research Institute)*

Corresponding author: **Jan Radosz**, jarad@ciop.pl

Noise, defined as the presence of undesirable sound, has been extensively documented in the context of its impact on human health. Exposure to elevated levels of acoustic pressure can result in adverse health outcomes such as hearing impairment, the perception of tinnitus, and various other health-related issues. In recent times, there has been a growing concern surrounding the potential health ramifications of exposure to ultrasonic noise. A number of countries have officially recognized ultrasonic noise as a health hazard within occupational settings. Despite ongoing investigations into the frequency range above 20 kHz, there remains a deficiency in comprehensive data pertaining to its effects on the human organism. Furthermore, there is a notable absence of internationally accepted standards for the assessment of ultrasonic noise within workplace environments. While recent research endeavors have contributed to the expansion of our understanding in this domain, there remains a substantial gap in knowledge. This deficiency encompasses inquiries into potential health consequences and the development of enhanced dosimetry methods. Moreover, this knowledge gap is particularly significant within the context of workplaces and the welfare of employees, underscoring the critical need to establish comprehensive measures that safeguard them against potential adverse health effects.